



PRODUCT-DETAILS

STC50/10M
TIN COP.BRDD S SUPERFLEX NC50 10MT



General Information	
Extended Product Type	STC50/10M
Product ID	7TCA296100R0211
EAN	5020963010514
Catalog Description	TIN COP.BRDD S SUPERFLEX NC50 10MT
Long Description	Low Fire Hazard, High Flexibility Conduit, 1-1/2 Inch, Nominal Conduit Size 50mm, Outside Diameter 56.0mm, Inside Diameter 48.4mm, Static Bend Radius 90mm, Reel Length 10 Meters, Galvanised Steel Core with Tinned Copper Overbraid

Additional Information	
Application	Galvanised Steel Core with Tinned Copper Overbraid
Product Type	Low Fire Hazard Conduit

Ordering	
EAN	5020963010514
UPC	786210260884

Dimensions	
Product Net Depth / Length	10 m

Technical	
Number of Batteries	0
Material	Galvanized Steel Core with Tinned Copper Overbraid

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	9.37 in 238 mm
Package Level 1 Depth / Length	19.25 in 489 mm
Package Level 1 Width	19.25 in 489 mm

Certificates and Declarations	
Data Sheet, Technical Information	STC50/10M
Instructions and Manuals	STC50/10M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

