TBM1100 1/3



PRODUCT-DETAILS

TBM1100 MEDIUM WALL 3:1 ADH.LINED



Extended Product Type	TBM1100
Product ID	7TCA017410R0009
EAN	5414363109426
Catalog Description	MEDIUM WALL 3:1 ADH.LINED
Long Description	Heat Shrink Tubing, Rated for 600 Volts, 90 Degree C, Continuous Use, RoHS Compliance, 27.9mm Expanded, 3 Per Bag, Black, Medium Wall, Adhesive Liner

Ordering	
E-Number (Finland)	5240648
EAN	5414363109426
UPC	786210082684
Country of Origin	Canada (CA)
Selling Unit of Measure	each

Dimensions	
Product Net Depth /	11.81 ft
Length	3.6 m

TBM1100 2/3

Container Information	
Package Level 1 Units	3 piece
Package Level 2 Units	75 piece
Package Level 2 Width	19.3 in 490 mm
Package Level 2 Height	6.7 in 170 mm
Package Level 2 Depth / Length	51.2 in 1300 mm

Additional Information	
Brand / Label	Shrink-Kon
Color	Black
Effective Date	19991228
Flammability Hazard Rating	Flame Retardant
Process Temperature Rating	-67 to +230 °F -55 to +110 °C
Product Name	PLASTIC CONDUIT
Product Type	Heat Shrinkable Tubing
RoHS Date	9AKK108466A7858
Shrink Ratio	3:1
Shrink Temperature	248 °F 120 °C

Certificates and Declarations	
Data Sheet, Technical Information	TBM1100

Classifications	
ETIM 6	EC000217 - Shrink tubing
ETIM 7	EC000217 - Shrink tubing
ETIM 8	EC000217 - Shrink tubing
UNSPSC	39121723
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5073 >> Heat shrinkable tube

Categories

TBM1100 3/3

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Installation\ Products\ \rightarrow\ Wire\ Management\ and\ Connectivity\ \rightarrow\ Identification\ \&\ Heat\ Shrink\ Analysis \ Analysis \$

