



PRODUCT-DETAILS

TBM2050
MID WALL 3:1 ADHES.LINED



General Information	
Extended Product Type	TBM2050
Product ID	7TCA017410R0014
EAN	5414363109464
Catalog Description	MID WALL 3:1 ADHES.LINED
Long Description	Heat Shrink Tubing, Rated for 600 Volts, 90 Degree C, Continuous Use, RoHS Compliance, 52.1mm Expanded, 1 Per Bag, Black, Medium Wall, Adhesive Liner

Ordering	
E-Number (Finland)	5240650
EAN	5414363109464
UPC	786210082721
Country of Origin	Canada (CA)
Selling Unit of Measure	each

Dimensions	
------------	--

Product Net Depth /	3.93 ft
Length	1.2 m

Container Information

Package Level 1 Units	1 piece
Package Level 2 Units	25 piece
Package Level 2 Width	17 in
	432 mm
Package Level 2 Height	12.5 in
	318 mm
Package Level 2 Depth /	50 in
Length	1270 mm

Additional Information

Brand / Label	Shrink-Kon
Color	Black
Effective Date	19991228
Flammability Hazard	Flame Retardant
Rating	
Process Temperature	-67 to +230 °F
Rating	-55 to +110 °C
Product Name	PLASTIC CONDUIT
Product Type	Heat Shrinkable Tubing
RoHS Date	9AKK108466A7858
Shrink Ratio	3:1
Shrink Temperature	248 °F
	120 °C

Certificates and Declarations

Data Sheet, Technical	TBM2050
Information	

Classifications

ETIM 6	EC000217 - Shrink tubing
ETIM 7	EC000217 - Shrink tubing
ETIM 8	EC000217 - Shrink tubing
UNSPSC	39121723
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category	5073 >> Heat shrinkable tube
Code (IGCC)	

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Identification & Heat Shrink

