TY125-40X-100 1/3



PRODUCT-DETAILS

TY125-40X-100 CBL TIE 40LB 5.5IN UV BLACK NYLON



General Information	
Extended Product Type	TY125-40X-100
Product ID	7TAG054360R0142
EAN	5414363075141
Catalog Description	CBL TIE 40LB 5.5IN UV BLACK NYLON
Long Description	Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius, Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/IEC 62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 143mm, Width of 3.6mm, Thickness of 1.2mm, Tensile Strength Rating of 180 Newtons, 100 Pack

Ordering	
E-Number (Finland)	1370041
EAN	5414363075141
UPC	786210073491
Country of Origin	Hungary (HU) United States (US)
Selling Unit of Measure	each

TY125-40X-100 2/3

Dimensions	
Product Net Width	6.1 m 0.24
Product Net Depth / Length	143 m 5.63
- Crigari	5.65
Container Information	
Package Level 1 Units	100 piec
Package Level 1 Width	4 i 102 mi
Package Level 1 Height	1.7 i 43 mi
Package Level 1 Depth / Length	7 i 178 mi
Package Level 2 Units	1000 piec
Package Level 2 Width	6.8 i
Package Level 2 Height	173 mi 7 i
	178 mr
Package Level 2 Depth /	8.5 i 216 mr
Technical UL/CSA Flammability According to UL94	
Technical UL/CSA Flammability According to UL94	V-
Technical UL/CSA Flammability According to UL94 Additional Information	V-
Technical UL/CSA Flammability According to UL94	V- Ty-Fa: 32 mi
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter	Ty-Fa: 32 mi 1.26
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color	Ty-Fa: 32 m: 1.26 i Blac
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date	Ty-Fa: 32 mr 1.26 i Blac 1993082
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type	V- Ty-Fa: 32 mr 1.26 i Blac 1993082 Plastic Pay
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material	V- Ty-Fa: 32 mr 1.26 i Blac 1993082 Plastic Pav Nylon/Polyamide 6.
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name Product Type	Ty-Fa 32 m 1.26 Blac 1993082 Plastic Pav Nylon/Polyamide 6 Plastic cable t General Purpos
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label	
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name Product Type Special Functions	Ty-Fas 32 mr 1.26 i Blac 1993082 Plastic Pav Nylon/Polyamide 6. Plastic cable ti General Purpos "The integrally formed polyamide pawl combines low insertion and high locking strength. The low profile head significantly reduces the potential for snagging during installation. Quick and easy pull through increases productivity, reduces operator fatigue. Tail with finger grip design that helps operator grasp and pul ties snugly. Sure grip tab keeps the tail from popping out while being treated
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name Product Type Special Functions Standards	Ty-Fa: 32 mr 1.26 i Blac 1993082 Plastic Pav Nylon/Polyamide 6. Plastic cable ti General Purpos "The integrally formed polyamide pawl combines low insertion and high locking strength. The low profile head significantly reduces the potential for snagging during installation. Quick and easy pull through increases productivity, reduces operator fatigue. Tail with finger grip design that helps operator grasp and pul ties snugly. Sure grip tab keeps the tail from popping out while being treated then holds it it securely for final tightening by hand or too UL E4940
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name Product Type	Ty-Fa: 32 mi 1.26 Blac 1993082 Plastic Pav Nylon/Polyamide 6. Plastic cable ti General Purpos "The integrally formed polyamide pawl combines low insertion and high locking strength. The low profile head significantly reduces the potential for snagging during installation. Quick and easy pull through increases productivity, reduce operator fatigue. Tail with finger grip design that helps operator grasp and puties snugly. Sure grip tab keeps the tail from popping out while being treated then holds it it securely for final tightening by hand or too UL E4940

Data Sheet, Technical Information

Declaration of Conformity

TDS000751

9AKK107492A9843

TY125-40X-100 3/3

Classifications	
ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
ETIM 8	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$

