



PRODUCT-DETAILS

TY175-50X
CBL TIE 50LB 7IN UV BLACK NYL



General Information

| | |
|-----------------------|--|
| Extended Product Type | TY175-50X |
| Product ID | 7TAG054360R0178 |
| EAN | 5414363060956 |
| Catalog Description | CBL TIE 50LB 7IN UV BLACK NYL |
| Long Description | Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius, Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/IEC 62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 188mm, Width of 4.7mm, Thickness of 1.2mm , Tensile Strength Rating of 220 Newtons, 1000 Pack |

Ordering

| | |
|-------------------------|---------------|
| E-Number (Finland) | 1370019 |
| EAN | 5414363060956 |
| UPC | 786210898575 |
| Country of Origin | Hungary (HU) |
| Selling Unit of Measure | each |

Dimensions

| | |
|----------------------------|----------------------|
| Product Net Width | 0.184 in 4.674 mm |
| Product Net Depth / Length | 188 mm 7.402 in |

Container Information

| | |
|--------------------------------|-------------------|
| Package Level 1 Units | 1000 piece |
| Package Level 2 Units | 10000 piece |
| Package Level 2 Width | 12.7 in 323 mm |
| Package Level 2 Height | 13.2 in 335 mm |
| Package Level 2 Depth / Length | 18.3 in 465 mm |

Technical UL/CSA

| | |
|--------------------------------|-----|
| Flammability According to UL94 | V-2 |
|--------------------------------|-----|

Additional Information

| | |
|-------------------|--|
| Brand / Label | Ty-Fast |
| Bundle Diameter | 44 mm 1.732 in |
| Color | Black |
| Effective Date | 19921030 |
| Lock Type | Plastic Pawl |
| Material | Nylon/Polyamide 6.6 Weather Resistant |
| Product Name | PLASTIC CABLE TIE |
| Product Type | General Purpose |
| Special Functions | "The integrally formed polyamide pawl combines low insertion and high locking strength. The low profile head significantly reduces the potential for snagging during installation. Quick and easy pull through increases productivity, reduces operator fatigue. Tail with finger grip design that helps operator grasp and pull ties snugly. Sure grip tab keeps the tail from popping out while being treated, then holds it it securely for final tightening by hand or tool" |
| Standards | UL E49405 |
| Tensile Strength | 222 N 50 lb |
| Thickness | 1.2 mm 0.047 in |

Certificates and Declarations

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | TDS000751 |
| Declaration of Conformity - CE | 9AKK107492A9843 |

Classifications

| | |
|------------------------|---------------------------|
| ETIM 6 | EC000046 - Cable tie |
| ETIM 7 | EC000046 - Cable tie |
| ETIM 8 | EC000046 - Cable tie |
| UNSPSC | 39121703 |
| WEEE Category | Product Not in WEEE Scope |
| IDEA Granular Category | 5034 >> Cable ties |

Code (IGCC) _____

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

