TY225-50 1/3



PRODUCT-DETAILS

TY225-50 CABLE TIE 50LB 9IN NATURAL NYLON



| General Information | |
|-----------------------|--|
| Extended Product Type | TY225-50 |
| Product ID | 7TCG054360R0230 |
| EAN | 5414363061335 |
| Catalog Description | CABLE TIE 50LB 9IN NATURAL NYLON |
| Long Description | Cable Tie, Natural Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius for Indoor Applications, UL/IEC 62275 Type 2/21 Rated for AH-2 Plenum, Length of 228mm, Width of 4.7mm, Thickness of 1.2mm, Tensile Strength Rating of 220 Newtons, 1000 Pack |

| Ordering | |
|-------------------------|---------------|
| EAN | 5414363061335 |
| UPC | 786210374321 |
| Country of Origin | Hungary (HU) |
| Selling Unit of Measure | each |

| Dimensions | |
|-------------------|--------------------|
| Product Net Width | 7.9 mm 0.311 in |

TY225-50 2/3

| Product Net Depth / | 228 mm | |
|--------------------------------------|--|------------|
| Length | 8.976 in | |
| | | |
| O f | | |
| Container Information | | |
| Package Level 1 Units | 1000 piece | |
| Package Level 1 Width | 1 in 25 mm | |
| Package Level 1 Height | 14 in | |
| | 356 mm | |
| Package Level 1 Depth / Length | 18 in 457 mm | |
| Package Level 2 Units | 10000 piece | |
| Package Level 2 Width | 15.4 in | |
| dokago Lovoi Z viidii | 391 mm | |
| Package Level 2 Height | 11 in | |
| Package Level 2 Depth / | 279 mm | |
| Package Level 2 Depth / Lenath | 23.6 in 599 mm | |
| | _ | |
| Technical UL/CSA | | |
| Flammability According to | V-2 | |
| UL94 | V-Z | |
| | | |
| | | |
| Additional Information | | |
| Additional Information | | |
| Brand / Label | Ty-Fast | |
| Bundle Diameter | 57 mm 2.244 in | |
| Color | 2.244 III Natural | |
| Effective Date | 19970425 | |
| Lock Type | Plastic Pawl | |
| Material | Nylon/Polyamide 6.6 | |
| Product Name | CATAMOUNT FASTENING PRODUCTS | |
| Product Type | General Purpose | |
| Special Functions | "The integrally formed polyamide pawl combines low insertion and high locking | |
| | strength. The low profile head significantly reduces the potential for snagging during installation. Quick and easy pull through increases productivity, reduces operator fatigue. Tail with finger grip design that helps operator grasp and pull ties snugly. Sure grip tab keeps the tail from popping out while being treated, then holds it it securely for final tightening by hand or too!" | |
| Standards | UL E49405 | |
| Tensile Strength | 222 N 50 lb | |
| Thickness | 1.2 mm | |
| | 0.047 in | |
| Cortification and Deplacations | | |
| Certificates and Declarations | | |
| Data Sheet, Technical Information | TDS000751 | |
| Declaration of Conformity - CE | 9AKK107492A9843 | |
| | | |
| Classifications | | |
| ETIM 6 | EC000046 - Cable tie | |
| ETIM 7 | EC000046 - Cable tie | |
| ETIM 8 | EC000046 - Cable tie | |
| © 2024 ABB. All rights reserved. | 2024/04/15 Subject to change | without no |
| 5 | , | |

TY225-50 3/3

 UNSPSC
 39121703

 WEEE Category
 Product Not in WEEE Scope

 IDEA Granular Category
 5034 >> Cable ties

 Code (IGCC)
 5034 >> Cable ties

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$

