TY242MX-RW 1/3



PRODUCT-DETAILS

TY242MX-RW TY242MX FOR RAILWAY

General Information	
Extended Product Type	TY242MX-RW
Product ID	7TCG009130R0011
EAN	5415022180107
Catalog Description	TY242MX FOR RAILWAY
Long Description	Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (221 F), Weather and Ultraviolet Resistant for Exterior Applications, Length of 208mm (8.19 Inches), Width of 3.6mm (0.142 Inches), Thickness of 1.04mm (0.041 Inches), Tensile Strength Rating of 180 Newtons (40 Pounds), Bulk Pack

Ordering	
EAN	5415022180107
UPC	786209699107
Country of Origin	Hungary (HU)
Selling Unit of Measure	each

Dimensions	
Product Net Width	0.14 in 3.71 mm

TY242MX-RW 2/3

Product Net Depth / 8.2 in Length 208.28 mm

Container Information	
Package Level 1 Units	1000 piece
Package Level 1 Width	10.61 in 269 mm
Package Level 1 Height	2.35 in 60 mm
Package Level 1 Depth / Length	11 in 279 mm
Package Level 2 Units	10000 piece
Package Level 2 Width	9.82 in 249 mm
Package Level 2 Height	9.03 in 229 mm
Package Level 2 Depth / Length	19.65 in 499 mm

Technical UL/CSA Flammability According to V-2 UL94 V-2

Additional Information	
Brand / Label	Ty-Rap
Bundle Diameter	2 in
	50.8 mm
Color	Black
Effective Date	20130729
Lock Type	Stainless Steel Barb
Material	Nylon/Polyamide 6.6
Product Name	OTHER ARTICLES OF PLASTIC
Product Type	High Performance
Special Functions	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.
Standards	UL E49405
Tensile Strength	40 lb 180 N

Certificates and Declarations	
Data Sheet, Technical	TY242MX-RW
Information	

Classifications	
ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
ETIM 8	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

TY242MX-RW 3/3

Categories

 $Low\ Voltage\ Products\ \rightarrow\ Installation\ Products\ \rightarrow\ Wire\ Management\ and\ Connectivity\ \rightarrow\ Cable\ Ties$

