TY244M-2 1/3



PRODUCT-DETAILS

TY244M-2CABLE TIE 30LB 14.5IN RED NYLON



General Information	
Extended Product Type	TY244M-2
Product ID	7TCG009160R0013
EAN	5414363062035
Catalog Description	CABLE TIE 30LB 14.5IN RED NYLON
Long Description	Cable Tie, Red Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, UL/EN/CSA62275 Type 2/21 Rated for AH-2 Plenum, Length of 368.3mm (14.5 Inches), Width of 3.51mm (0.138 Inch), Thickness of 0.75mm (0.03 Inch), Tensile Strength Rating of 134 Newtons (30 Pounds), Bulk Pack

Ordering	
EAN	5414363062035
UPC	786210714974
Country of Origin	Hungary (HU)
Selling Unit of Measure	each

Dimensions

TY244M-2 2/3

Product Net Width	0.138 in 3.51 mm
Product Net Depth / Length	14.5 in 368.3 mm

Container Information	
Package Level 1 Units	1000 piece
Package Level 2 Units	10000 piece
Package Level 2 Width	15.4 in 391 mm
Package Level 2 Height	11 in 279 mm
Package Level 2 Depth / Length	23.6 in 599 mm

Technical UL/CSA	
Flammability According	V-2
to UL94	

Additional Information	
Brand / Label	Ty-Rap
Bundle Diameter	0.08 to 4.05 in 2 to 102 mm
Color	Red
Effective Date	19710315
Lock Type	Stainless Steel Barb
Material	Nylon/Polyamide 6.6
Product Name	NYLON CABLE TIE
Product Type	High Performance
Special Functions	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.
Standards	UL E49405
Tensile Strength	30 lb 134 N
Thickness	0.041 in 1.04 mm

Certificates and Declarations	
Data Sheet, Technical Information	TY244M-2
Declaration of Conformity - CE	9AKK107492A9841

Classifications	
ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
ETIM 8	EC000046 - Cable tie
UNSPSC	39121703

TY244M-2 3/3

WEEE Category Product Not in WEEE Scope
IDEA Granular Category 5034 >> Cable ties
Code (IGCC)

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$

