TY244M 1/3



PRODUCT-DETAILS

TY244M CABLE TIE 30LB 14.5IN NAT NYLON

General Information	
Extended Product Type	TY244M
Product ID	7TCG009130R0005
EAN	5414363062004
Catalog Description	CABLE TIE 30LB 14.5IN NAT NYLON
Long Description	Cable Tie, Natural Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, UL/EN/CSA62275 Type 2/21 Rated for AH-2 Plenum, Length of 366mm (14.4 Inches), Width of 3.6mm (0.14 Inch), Thickness of 1 mm (0.04 Inch), Tensile

Ordering	
E-Number (Finland)	1381532
EAN	5414363062004
UPC	786210830728
Country of Origin	Hungary (HU)
Selling Unit of Measure	each

Dimensions

TY244M 2/3

Product Net Width	0.14 in 3.6 mm
Product Net Depth / Length	14.4 ir 366 mm
Container Information	
Package Level 1 Units	1000 piece
Package Level 2 Units	10000 piece
Package Level 2 Width	15.9 ir
Package Level 2 Height	404 mm 10.9 ir 277 mm
Package Level 2 Depth / Length	23.1 ir 587 mm
Technical UL/CSA	
Flammability According to UL94	V-2
Additional Information	
Brand / Label	Ty-Rap
Bundle Diameter	0.08 to 4.02 ir 2 to 102 mm
Color	Natura
Effective Date	19710315
Lock Type	Stainless Steel Barb
Material	Nylon/Polyamide 6.6
Product Name	NYLON CABLE TIE
Product Type	High Performance Low profile head is designed to prevent snags on uneven surfaces and easier
Special Functions	to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.
Standards	UL E49405
Tensile Strength	30 lb
Thickness	134 N 0.04 in 1.0 mm
Certificates and Declarations	
Data Sheet, Technical Information	TDS000566
Declaration of Conformity - CE	9AKK107492A9841
Classifications	
ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
ETIM 8	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category IDEA Granular Category	Product Not in WEEE Scope 5034 >> Cable ties
Code (IGCC)	3034 >> Cable lies

TY244M 3/3

S

 $Low\ Voltage\ Products\ \rightarrow\ Unstallation\ Products\ \rightarrow\ Wire\ Management\ and\ Connectivity\ \rightarrow\ Cable\ Ties$