TY244MX 1/3



PRODUCT-DETAILS

## **TY244MX**

## CABLE TIE 29LB 14.5IN UV BLACK NYL



| General Information   |  |
|-----------------------|--|
| Extended Product Type | TY244MX  |
| Product ID            | 7TCG009130R0006  |
| EAN                   | 5414363062097  |
| Catalog Description   | CABLE TIE 29LB 14.5IN UV BLACK NYL   |
| Long Description      | Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (220 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/EN/CSA62275 Type 2/21 Rated for AH-2 Plenum, Length of 366mm (14.4 Inches), Width of 3.6mm (0.14 Inch), Thickness of 1.15mm (0.045 Inch), Tensile Strength Rating of 130 Newtons (29 pounds), Bulk Pack |

| Ordering                |               |
|-------------------------|---------------|
| EAN                     | 5414363062097 |
| UPC                     | 786210878010  |
| Country of Origin       | Hungary (HU)  |
| Selling Unit of Measure | each          |

2/3 TY244MX

| Dimensions          |         |
|---------------------|---------|
| Product Net Width   | 0.14 in |
|                     | 3.6 mm  |
| Product Net Depth / | 14.4 in |
| Length              | 366 mm  |

| Container Information          |                   |
|--------------------------------|-------------------|
| Package Level 1 Units          | 1000 piece        |
| Package Level 2 Units          | 10000 piece       |
| Package Level 2 Width          | 17 in<br>432 mm   |
| Package Level 2 Height         | 10.9 in<br>277 mm |
| Package Level 2 Depth / Length | 23.3 in<br>592 mm |

| Technical UL/CSA                  |     |
|-----------------------------------|-----|
| Flammability According<br>to UL94 | V-2 |

| Additional Information |  |  |
|------------------------|--|--|
| Brand / Label          | Ty-Rap   |  |
| Bundle Diameter        | 0.08 to 4.02 in<br>2 to 102 mm   |  |
| Color                  | Black  |  |
| Effective Date         | 19710315   |  |
| Lock Type              | Stainless Steel Barb   |  |
| Material               | Nylon/Polyamide 6.6  |  |
| Product Name           | CABLE TIE  |  |
| Product Type           | High Performance   |  |
| Special Functions      | Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time. |  |
| Standards              | UL E49405  |  |
| Tensile Strength       | 29 lb<br>130 N   |  |
| Thickness              | 0.04 in<br>1.0 mm  |  |

| Certificates and Declarations        |                 |
|--------------------------------------|-----------------|
| Data Sheet, Technical<br>Information | TDS000566       |
| Declaration of<br>Conformity - CE    | 9AKK107492A9841 |

| Classifications |                      |
|-----------------|----------------------|
| ETIM 6          | EC000046 - Cable tie |
| ETIM 7          | EC000046 - Cable tie |
| ETIM 8          | EC000046 - Cable tie |

TY244MX 3/3

UNSPSC 39121703
WEEE Category Product Not in WEEE Scope
IDEA Granular Category 5034 >> Cable ties
Code (IGCC)

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$ 

