TY25M 1/3



PRODUCT-DETAILS

TY25M

CABLE TIE 50LB 7.31IN NATURAL NYLON

General Information	
Extended Product Type	TY25M
Product ID	7TAG009210R0042
EAN	5414363062448
Catalog Description	CABLE TIE 50LB 7.31IN NATURAL NYLON
Long Description	High Performance Cable Tie for Indoor applications, Natural Color Nylon 6.6, Length of 186mm (7.3 Inches) for Bundle Diameter up to 48mm (1.89 Inches), Width of 4.83mm (0.19 Inches), Tensile Strength Rating of 222 Newtons (50 Pounds), Operating Temperature of 60 Degrees Celsius (-76 F) to 85 Degrees Celsius (185 F), Bulk Pack

Ordering	
E-Number (Finland)	1370022
EAN	5414363062448
UPC	786210824574
Country of Origin	United States (US)
Selling Unit of Measure	each

Dimensions

TY25M 2/3

	0.19 i 4.9 mr
Product Net Depth / Length	7.2 i 183 mr
Container Information	
	1000 5
Package Level 1 Units Package Level 1 Width	1000 E/ 250.19 mr
Tuckage Level 1 Width	9.85 i
Package Level 1 Height	92.71 mr 3.65 i
Package Level 1 Depth /	344.17 mr
Length	13.55 i
Package Level 2 Width	10000 E. 342.9 mr
Package Level 2 Width	342.9 mi 13.5 i
Package Level 2 Height	246.38 mr 9.7 i
Package Level 2 Depth /	533.4 mr 21 i
Length Package Level 3 Units	350000 E.
Package Level 3 Width	0.025 mr
	0.001 ii
Package Level 3 Height	0.025 mn 0.001 i
Package Level 3 Depth / Length	0.025 mr 0.001 i
Environmental RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 201
Environmental RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Status Technical UL/CSA	
RoHS Status Technical UL/CSA Flammability According to	
Technical UL/CSA Flammability According to UL94	
Technical UL/CSA Flammability According to UL94 Additional Information	V-
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label	Ty-Ra 0.12 to 1.89 i
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter	Ty-Ra 0.12 to 1.89 i 3 to 48 mr
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color	Ty-Ra 0.12 to 1.89 i 3 to 48 mr Natura
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date	Ty-Ra 0.12 to 1.89 i 3 to 48 mr Natura 1968031
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material	V- Ty-Ra 0.12 to 1.89 i 3 to 48 mi Natura 1968031 Stainless Steel Bar Nylon/Polyamide 6.
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name	Ty-Ra 0.12 to 1.89 i 3 to 48 mr Natura 1968031 Stainless Steel Bar Nylon/Polyamide 6.
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name Product Type	Ty-Ra 0.12 to 1.89 i 3 to 48 mr Natura 1968031 Stainless Steel Bar Nylon/Polyamide 6. Othe High Performanc
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name Product Type	Ty-Ra 0.12 to 1.89 i 3 to 48 mi Natura 1968031 Stainless Steel Bar Nylon/Polyamide 6. Othe High Performanc Low profile head is designed to prevent snags on uneven surfaces and easie to pull through bulkheads. Non-magnetic stainless steel locking device insures
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name Product Type Special Functions	Ty-Ra 0.12 to 1.89 i 3 to 48 mr Natura 1968031 Stainless Steel Bar Nylon/Polyamide 6. Othe High Performanc Low profile head is designed to prevent snags on uneven surfaces and easie to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name	Ty-Ra 0.12 to 1.89 i 3 to 48 mr Natura 1968031 Stainless Steel Bar Nylon/Polyamide 6. Othe High Performanc Low profile head is designed to prevent snags on uneven surfaces and easie to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time UL E49405, CSA 288
Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name Product Type Special Functions Standards	Ty-Ra 0.12 to 1.89 i 3 to 48 mr Natura 1968031 Stainless Steel Bar Nylon/Polyamide 6. Othe High Performanc Low profile head is designed to prevent snags on uneven surfaces and easie to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time UL E49405, CSA 288

TY25M 3/3

Certificates and Declarations		
Data Sheet, Technical Information	TDS000518	
Declaration of Conformity - CF	9AKK107492A9841	

Classifications	
ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
ETIM 8	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Installation\ Products\ \rightarrow\ Wire\ Management\ and\ Connectivity\ \rightarrow\ Cable\ Ties$

