TY275M 1/3



PRODUCT-DETAILS

TY275M

CABLE TIE 120LB 18IN NATURAL NYLON

| General Information | |
|-----------------------|--|
| Extended Product Type | TY275M |
| Product ID | 7TAG009330R0009 |
| EAN | 5414363063094 |
| Catalog Description | CABLE TIE 120LB 18IN NATURAL NYLON |
| Long Description | High Performance Cable Tie, Natural Color Nylon 6.6, Length of 457mm (18 Inches) for Bundle Diameter up to 127mm (5 Inches), Width of 6.9mm (0.27 Inch), Tensile Strength Rating of 534 Newtons (120 Pounds), Operating Temperature of -20 Degrees Celsius (-4 F) to 85 Degrees Celsius (185 F), Bulk Pack |

| Ordering | | |
|-------------------------|--------------------|--|
| EAN | 5414363063094 | |
| UPC | 786210870793 | |
| Country of Origin | United States (US) | |
| Selling Unit of Measure | each | |

| 0.27 in |
|---------|
| |

TY275M 2/3

| Product Net Depth / | 18 in |
|---------------------|--------|
| Length | 457 mm |

| Container Information | |
|-----------------------------------|----------------------|
| Package Level 1 Units | 500 EA |
| Package Level 1 Width | 233.68 mm 9.2 in |
| Package Level 1 Height | 193.04 mm 7.6 in |
| Package Level 1 Depth / Length | 561.34 mm 22.1 in |
| Package Level 2 Units | 24000 EA |
| Package Level 2 Width | 0 mm 0 in |
| Package Level 2 Height | 0 mm 0 in |
| Package Level 2 Depth / Length | 0 mm <u>0 in</u> |

Environmental

RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Technical UL/CSA

Flammability According to V-2 UL94

| Additional Information | |
|------------------------|--|
| Brand / Label | Ty-Rap |
| Bundle Diameter | Max 5 in Max 127 mm |
| Color | Natural |
| Effective Date | 19900615 |
| Lock Type | Stainless Steel Barb |
| Material | Nylon/Polyamide 6.6 |
| Product Name | Other /note: See 9903.88.66 and 9903.88. 67. |
| Product Type | High Performance |
| Special Functions | Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time. |
| Standards | UL E49405 |
| Tensile Strength | 120 lb 534 N |
| Thickness | 0.06 in |

| Certificates and Declarations | |
|--------------------------------------|-----------------|
| Data Sheet, Technical Information | TDS000487 |
| Declaration of Conformity - CE | 9AKK107492A9841 |

Classifications

1.5 mm

TY275M 3/3

| ETIM 6 | EC000046 - Cable tie |
|---------------------------------------|---------------------------|
| ETIM 7 | EC000046 - Cable tie |
| ETIM 8 | EC000046 - Cable tie |
| UNSPSC | 39121703 |
| WEEE Category | Product Not in WEEE Scope |
| IDEA Granular Category Code (IGCC) | 5034 >> Cable ties |

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Installation\ Products\ \rightarrow\ Wire\ Management\ and\ Connectivity\ \rightarrow\ Cable\ Ties$