TY27MX-A 1/3



PRODUCT-DETAILS

TY27MX-A

CABLE TIE 120LB 13IN BK NYL HT STB



General Information	
Extended Product Type	TY27MX-A
Product ID	7TAG009640R0003
EAN	5414363063421
Catalog Description	CABLE TIE 120LB 13IN BK NYL HT STB
Long Description	Cable Tie, Heat Stabilized, Ultraviolet Resistant Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (221 F) for Indoor or Outdoor Applications, UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 340mm (13.4 Inches), Width of 6.86mm (0.27 Inches), Thickness of 1.6mm (0.063 Inches), Tensile Strength Rating of 540 Newtons (120 Pounds)

Ordering	
EAN	5414363063421
UPC	786210816425
Country of Origin	United States (US)
Selling Unit of Measure	each

TY27MX-A 2/3

Dimensions	
Product Net Width	0.27 in 6.86 mm
Product Net Depth / Length	13.5 in 343 mm

Container Information	
Package Level 1 Units	500 EA
Package Level 1 Width	355.6 mm 14 in
Package Level 1 Height	25.4 mm 1 in
Package Level 1 Depth / Length	558.8 mm 22 in
Package Level 2 Units	1000 EA
Package Level 2 Width	127 mm 5 in
Package Level 2 Height	241.3 mm 9.5 in
Package Level 2 Depth / Length	387.35 mm 15.25 in
Package Level 3 Units	104000 EA
Package Level 3 Width	0.025 mm 0.001 in
Package Level 3 Height	0.025 mm 0.001 in
Package Level 3 Depth / Length	0.025 mm 0.001 in

Environmental	
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Technical UL/CSA	
Flammability According	V-2
to UL94	

Additional Information	
Brand / Label	Ty-Rap
Bundle Diameter	0.31 to 3.74 in 8 to 95 mm
Color	Black
Effective Date	20020129
Lock Type	Stainless Steel Barb
Material	Nylon/Polyamide 6.6
Product Name	Other /note: See 9903.88.66 and 9903.88. 67.
Product Type	Heat-Stabilized
RoHS Date	9AKK108466A3874
Special Functions	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.

TY27MX-A 3/3

Standards	UL E49405
Tensile Strength	121.4 lb
	540 N
Thickness	0.06 in
	1.6 mm

Certificates and Declarations	
Data Sheet, Technical	TDS000494
Information	

Classifications	
ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
ETIM 8	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$

