TY400-120X-100 1/3



PRODUCT-DETAILS

TY400-120X-100

CBL TIE 120LB 15IN UV BLACK NYLON



| General Information | |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | TY400-120X-100 |
| Product ID | 7TCG054360R0308 |
| EAN | 5414363075349 |
| Catalog Description | CBL TIE 120LB 15IN UV BLACK NYLON |
| Long Description | "Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius, Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/IEC 62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 374mm, Width of 7.6mm, Thickness of 1.9mm, Tensile Strength Rating of 540 Newtons, 100 Pack" |

| Ordering | |
|-------------------------|------------------------------------|
| EAN | 5414363075349 |
| UPC | 786210627830 |
| Country of Origin | Hungary (HU) United States (US) |
| Selling Unit of Measure | each |

TY400-120X-100 2/3

| Dimensions | |
|---------------------|-----------|
| Product Net Width | 12.2 mm |
| | 0.48 in |
| Product Net Depth / | 374 mm |
| Length | 14.724 in |

| Container Information | |
|-----------------------------------|-----------------|
| Package Level 1 Units | 100 piece |
| Package Level 2 Units | 2500 piece |
| Package Level 2 Width | 8 in 203 mm |
| Package Level 2 Height | 10 in 254 mm |
| Package Level 2 Depth / Length | 24 in 610 mm |

| Technical UL/CSA | |
|-----------------------------------|-----|
| Flammability According to UL94 | V-2 |

| Additional Information | |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Brand / Label | Ty-Fast |
| Bundle Diameter | 103.1 mm |
| | 4.059 in |
| Color | Black |
| Effective Date | 19980621 |
| Lock Type | Plastic Pawl |
| Material | Nylon/Polyamide 6.6 |
| Product Name | PLASTIC CABLE TIE |
| Product Type | General Purpose |
| Special Functions | "The integrally formed polyamide pawl combines low insertion and high locking strength. The low profile head significantly reduces the potential for snagging during installation. Quick and easy pull through increases productivity, reduces operator fatigue. Tail with finger grip design that helps operator grasp and pull ties snugly. Sure grip tab keeps the tail from popping out while being treated, then holds it it securely for final |
| | tightening by hand or tool" |
| Standards | UL E49405 |
| Tensile Strength | 540 N 121 lb |
| Thickness | 1.9 mm 0.075 in |

| Certificates and Declarations | |
|--------------------------------------|-----------------|
| Data Sheet, Technical Information | TDS000751 |
| Declaration of Conformity - CE | 9AKK107492A9843 |

Classifications

TY400-120X-100 3/3

| ETIM 6 | EC000046 - Cable tie |
|---------------------------------------|---------------------------|
| ETIM 7 | EC000046 - Cable tie |
| ETIM 8 | EC000046 - Cable tie |
| UNSPSC | 39121703 |
| WEEE Category | Product Not in WEEE Scope |
| IDEA Granular Category Code (IGCC) | 5034 >> Cable ties |

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$

