TY400-50-100 1/3



PRODUCT-DETAILS

TY400-50-100

CABLE TIE 50LB 14IN NATURAL NYL



| General Information | |
|-----------------------|--|
| Extended Product Type | TY400-50-100 |
| Product ID | 7TAG054360R0316 |
| EAN | 5414363064619 |
| Catalog Description | CABLE TIE 50LB 14IN NATURAL NYL |
| Long Description | Cable Tie, Natural Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius for Indoor Applications, UL/IEC 62275 Type 2/21 Rated for AH-2 Plenum, Length of 365mm, Width of 4.7mm, Thickness of 1.2mm, Tensile Strength Rating of 220 Newtons, 100 Pack |

| Ordering | |
|-------------------------|-----------------------------|
| EAN | 5414363064619 |
| UPC | 786210918037 |
| Country of Origin | Hungary (HU) Mexico (MX) |
| Selling Unit of Measure | each |

TY400-50-100 2/3

| Dimensions | |
|---------------------|----------|
| Product Net Width | 7.9 mm |
| | 0.311 in |
| Product Net Depth / | 365 mm |
| Length | 14.37 in |

| Container Information | |
|-----------------------------------|-------------------|
| Package Level 1 Units | 100 piece |
| Package Level 1 Width | 13.2 in 335 mm |
| Package Level 1 Height | 8.8 in 224 mm |
| Package Level 1 Depth / Length | 22.2 in 564 mm |
| Package Level 2 Units | 5000 piece |
| Package Level 2 Width | 5.5 in 140 mm |
| Package Level 2 Height | 5.5 in 140 mm |
| Package Level 2 Depth / Length | 15.3 in 389 mm |

| Technical UL/CSA | |
|------------------------|-----|
| Flammability According | V-2 |
| to UL94 | |

| Additional Information | |
|------------------------|--|
| Brand / Label | Ty-Fast |
| Bundle Diameter | 102 mm |
| | 4.016 in |
| Color | Natural |
| Effective Date | 19930630 |
| Lock Type | Plastic Pawl |
| Material | Nylon/Polyamide 6.6 |
| Product Name | PLASTIC CABLE TIE |
| Product Type | General Purpose |
| Special Functions | "The integrally formed polyamide pawl combines low insertion and high locking strength. The low profile head significantly reduces the potential for snagging during installation. Quick and easy pull through increases productivity, reduces operator fatigue. Tail with finger grip design that helps operator grasp and pull ties snugly. Sure grip tab keeps the tail from popping out while being treated, then holds it it securely for final tightening by hand or tool" |
| Standards | UL E49405 |
| Tensile Strength | 222 N 50 lb |
| Thickness | 1.2 mm 0.047 in |

| Certificates and Declarations | |
|-------------------------------|-----------|
| Data Sheet, Technical | TDS000751 |
| Information | |

TY400-50-100 3/3

Declaration of 9AKK107492A9843
Conformity - CE

| Classifications | |
|---------------------------------------|---------------------------|
| ETIM 6 | EC000046 - Cable tie |
| ETIM 7 | EC000046 - Cable tie |
| ETIM 8 | EC000046 - Cable tie |
| UNSPSC | 39121703 |
| WEEE Category | Product Not in WEEE Scope |
| IDEA Granular Category Code (IGCC) | 5034 >> Cable ties |

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$

