



PRODUCT-DETAILS

TY400-50X-100

CBL TIE 14IN UV BLACK NYL 50LB



| General Information | |
|-------------------------|---|
| Extended Product Type | TY400-50X-100 |
| Product ID | 7TAG054360R0337 |
| EAN | 5414363075363 |
| Catalog Description | CBL TIE 14IN UV BLACK NYL 50LB |
| Long Description | Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius, Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/IEC 62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 365mm, Width of 4.7mm, Thickness of 1.2mm , Tensile Strength Rating of 220 Newtons, 100 Pack |
| Ordering | |
| EAN | 5414363075363 |
| UPC | 075114952392 |
| Country of Origin | Hungary (HU) United States (US) Mexico (MX) |
| Selling Unit of Measure | each |

| | |
|----------------------------|---------------------|
| Dimensions | |
| Product Net Width | 4.7 mm 0.188 in |
| Product Net Depth / Length | 366 mm 14.409 in |

| | |
|--------------------------------|-------------------|
| Container Information | |
| Package Level 1 Units | 100 piece |
| Package Level 1 Width | 6 in 152 mm |
| Package Level 1 Height | 1.7 in 43 mm |
| Package Level 1 Depth / Length | 18 in 457 mm |
| Package Level 2 Units | 5000 piece |
| Package Level 2 Width | 5.8 in 147 mm |
| Package Level 2 Height | 5.6 in 142 mm |
| Package Level 2 Depth / Length | 15.4 in 391 mm |

| | |
|--------------------------------|-----|
| Technical UL/CSA | |
| Flammability According to UL94 | V-2 |

| | |
|-------------------------------|--|
| Additional Information | |
| Brand / Label | Ty-Fast |
| Bundle Diameter | 102 mm 4.016 in |
| Color | Black |
| Effective Date | 19930820 |
| Lock Type | Plastic Pawl |
| Material | Nylon/Polyamide 6.6 |
| Product Name | PLASTIC CABLE TIE |
| Product Type | General Purpose |
| Special Functions | "The integrally formed polyamide pawl combines low insertion and high locking strength. The low profile head significantly reduces the potential for snagging during installation. Quick and easy pull through increases productivity, reduces operator fatigue. Tail with finger grip design that helps operator grasp and pull ties snugly. Sure grip tab keeps the tail from popping out while being treated, then holds it it securely for final tightening by hand or tool" |
| Standards | UL E49405 |
| Tensile Strength | 222 N 50 lb |
| Thickness | 1.2 mm 0.047 in |

| | |
|--------------------------------------|-----------------|
| Certificates and Declarations | |
| Data Sheet, Technical Information | TDS000751 |
| Declaration of Conformity - CE | 9AKK107492A9843 |

| Classifications | |
|------------------------------------|---------------------------|
| ETIM 6 | EC000046 - Cable tie |
| ETIM 7 | EC000046 - Cable tie |
| ETIM 8 | EC000046 - Cable tie |
| UNSPSC | 39121703 |
| WEEE Category | Product Not in WEEE Scope |
| IDEA Granular Category Code (IGCC) | 5034 >> Cable ties |

| Categories |
|--|
| Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties |

