TY400-50X 1/3



PRODUCT-DETAILS

TY400-50X CBL TIE 50LB 14IN UV BLACK NYL



General Information	
Extended Product Type	TY400-50X
Product ID	7TAG054360R0336
EAN	5414363064756
Catalog Description	CBL TIE 50LB 14IN UV BLACK NYL
Long Description	Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius, Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/IEC 62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 365mm, Width of 4.7mm, Thickness of 1.2mm, Tensile Strength Rating of 220 Newtons, 1000 Pack

Ordering	
E-Number (Finland)	1381500
EAN	5414363064756
UPC	786210898599
Country of Origin	Hungary (HU) Mexico (MX)
Selling Unit of Measure	each

TY400-50X 2/3

Dimensions	
Product Net Width	7.9 mm
	0.311 in
Product Net Depth / Length	366 mm 14.409 in
Container Information	
	1000
Package Level 1 Units	
Package Level 1 Width	533 mm
Package Level 1 Height	4 in 102 mm
Package Level 1 Depth / Length	15 in 381 mm
Package Level 2 Units	5000 piece
Package Level 2 Width	13.1 in 333 mm
Package Level 2 Height	15.5 in 394 mm
Package Level 2 Depth / Length	19.6 in 498 mm
Technical UL/CSA	
r cerimical of 7007 (
Flammability According to UL94	V-2
Flammability According to	V-2
Flammability According to UL94	
Flammability According to UL94 Additional Information	Ty-Fast 102 mm
Flammability According to UL94 Additional Information Brand / Label	Ty-Fast 102 mm 4.016 in
Flammability According to UL94 Additional Information Brand / Label Bundle Diameter	Ty-Fast 102 mm 4.016 in Black
Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color	Ty-Fast 102 mm 4.016 in Black 19921030
Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material	Ty-Fast 102 mm 4.016 in Black 19921030 Plastic Pawl Nylon/Polyamide 6.6 Weather Resistant
Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name	Ty-Fast 102 mm 4.016 in Black 19921030 Plastic Pawl Nylon/Polyamide 6.6 Weather Resistant
Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name Product Type	Ty-Fast 102 mm 4.016 in Black 19921030 Plastic Pawl Nylon/Polyamide 6.6 Weather Resistant PLASTIC CABLE TIE General Purpose
Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name	Ty-Fast 102 mm 4.016 in Black 19921030 Plastic Pawl Nylon/Polyamide 6.6 Weather Resistant PLASTIC CABLE TIE General Purpose "The integrally formed polyamide pawl combines low insertion and high locking strength. The low profile head significantly reduces the potential for snagging during installation. Quick and easy pull through increases productivity, reduces operator fatigue. Tail with finger grip design that helps operator grasp and pull ties snugly. Sure grip tab keeps the tail from popping out while being treated, then holds it it securely for final tightening by hand or tool"
Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name Product Type	Ty-Fast 102 mm 4.016 in Black 19921030 Plastic Pawl Nylon/Polyamide 6.6 Weather Resistant PLASTIC CABLE TIE General Purpose "The integrally formed polyamide pawl combines low insertion and high locking strength. The low profile head significantly reduces the potential for snagging during installation. Quick and easy pull through increases productivity, reduces operator fatigue. Tail with finger grip design that helps operator grasp and pull ties snugly. Sure grip tab keeps the tail from popping out while being treated,
Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name Product Type Special Functions	Ty-Fast 102 mm 4.016 in Black 19921030 Plastic Pawl Nylon/Polyamide 6.6 Weather Resistant PLASTIC CABLE TIE General Purpose "The integrally formed polyamide pawl combines low insertion and high locking strength. The low profile head significantly reduces the potential for snagging during installation. Quick and easy pull through increases productivity, reduces operator fatigue. Tail with finger grip design that helps operator grasp and pull ties snugly. Sure grip tab keeps the tail from popping out while being treated, then holds it it securely for final tightening by hand or tool" UL E49405
Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name Product Type Special Functions Standards	Ty-Fast 102 mm 4.016 in Black 19921030 Plastic Paw Nylon/Polyamide 6.6 Weather Resistant PLASTIC CABLE TIE General Purpose "The integrally formed polyamide pawl combines low insertion and high locking strength. The low profile head significantly reduces the potential for snagging during installation. Quick and easy pull through increases productivity, reduces operator fatigue. Tail with finger grip design that helps operator grasp and pull ties snugly. Sure grip tab keeps the tail from popping out while being treated, then holds it it securely for final tightening by hand or tool' UL E49405 222 N 50 lb
Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name Product Type Special Functions Standards Tensile Strength Thickness	Ty-Fast 102 mm 4.016 in Black 19921030 Plastic Paw Nylon/Polyamide 6.6 Weather Resistant PLASTIC CABLE TIE General Purpose "The integrally formed polyamide pawl combines low insertion and high locking strength. The low profile head significantly reduces the potential for snagging during installation. Quick and easy pull through increases productivity, reduces operator fatigue. Tail with finger grip design that helps operator grasp and pull ties snugly. Sure grip tab keeps the tail from popping out while being treated, then holds it it securely for final tightening by hand or tool' UL E49405 222 N 50 lb
Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name Product Type Special Functions Standards Tensile Strength Thickness Certificates and Declarations Data Sheet, Technical	Ty-Fast 102 mm 4.016 in Black 19921030 Plastic Pawl Nylon/Polyamide 6.6 Weather Resistant PLASTIC CABLE TIE General Purpose "The integrally formed polyamide pawl combines low insertion and high locking strength. The low profile head significantly reduces the potential for snagging during installation. Quick and easy pull through increases productivity, reduces operator fatigue. Tail with finger grip design that helps operator grasp and pull ties snugly. Sure grip tab keeps the tail from popping out while being treated, then holds it it securely for final tightening by hand or tool" UL E49405 222 N 50 lb 1.2 mm 0.047 in
Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name Product Type Special Functions Standards Tensile Strength Thickness Certificates and Declarations	Ty-Fast 102 mm 4.016 in Black 19921030 Plastic Pawl Nylon/Polyamide 6.6 Weather Resistant PLASTIC CABLE TIE General Purpose "The integrally formed polyamide pawl combines low insertion and high locking strength. The low profile head significantly reduces the potential for snagging during installation. Quick and easy pull through increases productivity, reduces operator fatigue. Tail with finger grip design that helps operator grasp and pull ties snugly. Sure grip tab keeps the tail from popping out while being treated, then holds it it securely for final tightening by hand or tool"

TY400-50X 3/3

Classifications	
ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
ETIM 8	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$

