TY5234M 1/3



PRODUCT-DETAILS

TY5234M CBL TIE 18LB 14IN NATURAL NYLON



| General Information | |
|-----------------------|---|
| Extended Product Type | TY5234M |
| Product ID | 7TAG009020R0052 |
| EAN | 5414363065326 |
| Catalog Description | CBL TIE 18LB 14IN NATURAL NYLON |
| Long Description | Cable Tie, Natural Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, UL/EN/CSA62275 Type 2/21 Rated for AH-2 Plenum, Length of 357mm (14 Inches), Width of 2.3mm (0.09 Inches), Thickness of 1.1mm (0.04 Inches), Tensile Strength Rating of 80 Newtons (18 Pounds) |

| Ordering | |
|--------------------------|--------------------|
| EAN | 5414363065326 |
| UPC | 786210830780 |
| Country of Origin | United States (US) |
| Calling Unit of Managera | anah |

| Dimensions | |
|-------------------|-------------------|
| Product Net Width | 0.09 in 2.3 mm |

TY5234M 2/3

| Product Net Depth / | 14 in |
|---------------------|--------|
| Length | 357 mm |

| Container Information | |
|-----------------------------------|---------------------|
| Package Level 1 Units | 100 EA |
| Package Level 1 Width | 85.09 mm 3.35 in |
| Package Level 1 Height | 60.96 mm 2.4 in |
| Package Level 1 Depth / Length | 381 mm 15 in |
| Package Level 2 Units | 500 EA |
| Package Level 2 Width | 139.7 mm 5.5 in |
| Package Level 2 Height | 134.62 mm 5.3 in |
| Package Level 2 Depth / Length | 381 mm 15 in |
| Package Level 3 Units | 96000 EA |
| Package Level 3 Width | 0 mm 0 in |
| Package Level 3 Height | 0 mm 0 in |
| Package Level 3 Depth / Length | 0 mm 0 in |

Environmental

RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Technical UL/CSA

Flammability According to V-2 UL94

Additional Information

| Brand / Label | Ty-Rap |
|-------------------|--|
| Bundle Diameter | 0.06 to 4.2 in 1.5 to 102 mm |
| Color | Natural |
| Effective Date | 19710405 |
| Lock Type | Stainless Steel Barb |
| Material | Nylon/Polyamide 6.6 |
| Product Name | Other /note: See 9903.88.66 and 9903.88. 67. |
| Product Type | High Performance |
| Special Functions | Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time. |
| Standards | UL E49405 |
| Tensile Strength | 18 lb 80 N |
| Thickness | 0.04 in 1 mm |

Certificates and Declarations

Data Sheet, Technical TDS000570

TY5234M 3/3

Information

| Declaration of Conformity | 9AKK107492A9841 |
|---------------------------|-----------------|
| - CF | |

| Classifications | |
|---------------------------------------|---------------------------|
| ETIM 6 | EC000046 - Cable tie |
| ETIM 7 | EC000046 - Cable tie |
| ETIM 8 | EC000046 - Cable tie |
| UNSPSC | 39121703 |
| WEEE Category | Product Not in WEEE Scope |
| IDEA Granular Category Code (IGCC) | 5034 >> Cable ties |

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$

