



PRODUCT-DETAILS

TY525MXR

CBL TIE 50LB 7IN UV BLACK NYL



| General Information | |
|-----------------------|---|
| Extended Product Type | TY525MXR |
| Product ID | 7TCG009200R0023 |
| EAN | 5414363065661 |
| Catalog Description | CBL TIE 50LB 7IN UV BLACK NYL |
| Long Description | Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (222 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 185.67mm (7.31 Inches), Width of 4.9mm (0.19 Inches), Thickness of 1.09mm (0.043 Inches), Tensile Strength Rating of 222 Newtons (50 Pounds), Euroslot Packaging |

| Ordering | |
|-------------------------|---------------|
| E-Number (Finland) | 1370009 |
| EAN | 5414363065661 |
| UPC | 786210378527 |
| Country of Origin | Hungary (HU) |
| Selling Unit of Measure | each |

Dimensions

| | |
|----------------------------|---------------------|
| Product Net Width | 0.184 in 4.67 mm |
| Product Net Depth / Length | 7.2 in 183 mm |

Container Information

| | |
|--------------------------------|-------------------|
| Package Level 1 Units | 100 piece |
| Package Level 2 Units | 10000 piece |
| Package Level 2 Width | 8 in 203 mm |
| Package Level 2 Height | 6.5 in 165 mm |
| Package Level 2 Depth / Length | 9.75 in 248 mm |

Technical UL/CSA

| | |
|--------------------------------|-----|
| Flammability According to UL94 | V-2 |
|--------------------------------|-----|

Additional Information

| | |
|-------------------|--|
| Brand / Label | Ty-Rap |
| Bundle Diameter | 0.12 to 1.89 in 3 to 48 mm |
| Color | Black |
| Effective Date | 19980621 |
| Lock Type | Stainless Steel Barb |
| Material | Nylon/Polyamide 6.6 |
| Product Name | TY-RAP FASTENING |
| Product Type | High Performance |
| RoHS Date | 9AKK107991A8361 |
| Special Functions | Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time. |
| Tensile Strength | 50 lb 222 N |
| Thickness | 0.04 in 1.1 mm |

Certificates and Declarations

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | TDS000518 |
| Declaration of Conformity - CE | 9AKK107492A9841 |

Classifications

| | |
|--------|----------------------|
| ETIM 6 | EC000046 - Cable tie |
| ETIM 7 | EC000046 - Cable tie |

| | |
|------------------------------------|---------------------------|
| ETIM 8 | EC000046 - Cable tie |
| UNSPSC | 39121703 |
| WEEE Category | Product Not in WEEE Scope |
| IDEA Granular Category Code (IGCC) | 5034 >> Cable ties |

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

