TY5277MX 1/3



PRODUCT-DETAILS

# TY5277MX CBL TIE 120LB 24.3IN UV BLACK NYLON

| General Information   |   |
|-----------------------|---|
| Extended Product Type | TY5277MX  |
| Product ID            | 7TAG009290R0006   |
| EAN                   | 5414363065821   |
| Catalog Description   | CBL TIE 120LB 24.3IN UV BLACK NYLON   |
| Long Description      | High Performance Cable Tie, Black Color Nylon 6.6, Length of 617mm (24.3 Inches) for Bundle Diameter up to 177 mm (6.97 Inches), Width of 6.86mm (0.27 Inch), Tensile Strength Rating of 534 Newtons (120 Pounds), Operating Temperature of -60 Degrees Celsius (-76F) to 85 Degrees Celsius (185). |

| Ordering                |                    |
|-------------------------|--------------------|
| EAN                     | 5414363065821      |
| UPC                     | 786210870861       |
| Country of Origin       | United States (US) |
| Selling Unit of Measure | each               |

| 0.27 in |
|---------|
|         |

TY5277MX 2/3

| Product Net Depth / | 24.3 in |
|---------------------|---------|
| Length              | 617 mm  |

| Container Information             |                      |
|-----------------------------------|----------------------|
| Package Level 1 Units             | 50 EA                |
| Package Level 1 Width             | 152.4 mm<br>6 in     |
| Package Level 1 Height            | 44.45 mm<br>1.75 in  |
| Package Level 1 Depth / Length    | 736.6 mm<br>29 in    |
| Package Level 2 Units             | 500 EA               |
| Package Level 2 Width             | 237.49 mm<br>9.35 in |
| Package Level 2 Height            | 147.32 mm<br>5.8 in  |
| Package Level 2 Depth / Length    | 817.88 mm<br>32.2 in |
| Package Level 3 Units             | 24500 EA             |
| Package Level 3 Width             | 0 mm<br>0 in         |
| Package Level 3 Height            | 0 mm<br>0 in         |
| Package Level 3 Depth /<br>Length | 0 mm<br>0 in         |

#### Environmental

RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

## Technical UL/CSA

Flammability According to V-2 UL94

# **Additional Information**

| Brand / Label     | Ty-Rap   |
|-------------------|--|
| Bundle Diameter   | Max 6.97 in<br>Max 177 mm  |
| Color             | Black  |
| Effective Date    | 19900615   |
| Lock Type         | Stainless Steel Barb   |
| Material          | Nylon/Polyamide 6.6  |
| Product Name      | Other /note: See 9903.88.66 and 9903.88. 67.   |
| Product Type      | High Performance   |
| Special Functions | Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time. |
| Standards         | UL E49405  |
| Tensile Strength  | 120 lb<br>534 N  |
| Thickness         | 0.06 in<br>1.5 mm  |

## Certificates and Declarations

Data Sheet, Technical TDS000487

TY5277MX 3/3

Information

| Declaration of Conformity | 9AKK107492A9841 |
|---------------------------|-----------------|
| - CF                      |                 |

| Classifications                       |                           |
|---------------------------------------|---------------------------|
| ETIM 6                                | EC000046 - Cable tie      |
| ETIM 7                                | EC000046 - Cable tie      |
| ETIM 8                                | EC000046 - Cable tie      |
| UNSPSC                                | 39121703                  |
| WEEE Category                         | Product Not in WEEE Scope |
| IDEA Granular Category<br>Code (IGCC) | 5034 >> Cable ties        |

# Categories

 $Low\ Voltage\ Products\ \rightarrow\ Unstallation\ Products\ \rightarrow\ Wire\ Management\ and\ Connectivity\ \rightarrow\ Cable\ Ties$ 

