



PRODUCT-DETAILS

XSOLLG-48BG.30
COND CRSE PA12/6 NW48 30M BLK/GN



General Information	
Extended Product Type	XSOLLG-48BG.30
Product ID	7TAA292240R0312
EAN	7630030282058
Catalog Description	COND CRSE PA12/6 NW48 30M BLK/GN
Long Description	Coarse Profile Three Layer Corrugated Medium-Wall Highly Flexible Conduit, (XSOLL) Material - Outer Layer - Polyamide 12, Intermediate Layer - Bonding Compound, Inner Layer - Polyamide 6, Color - Outer Layer - Black, Inner Layer - Green, Conduit Size NW - 48, 30 Meters

Additional Information	
Application	Building Construction
Product Type	Medium Wall Conduit

Ordering	
EAN	7630030282058
UPC	786209977939

Dimensions	
Product Net Depth / Length	30 m

Technical	
Number of Batteries	0
Color	Black
Material	Outer Layer Polamide 12, Inner Layer Polyamide 6

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	30 m
Package Level 1 Height	0 mm 0 in
Package Level 1 Depth / Length	0 mm 0 in
Package Level 1 Width	0 mm 0 in

Certificates and Declarations	
Data Sheet, Technical Information	XSOLLG-48BG.30
Instructions and Manuals	XSOLLG-48BG.30
Declaration of Conformity - CE	9AKK107680A0674

Classifications	
ETIM 8	EC001175 - Corrugated plastic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

