



PRODUCT-DETAILS

XSOLT-12BG.50
CONDUIT FINE PA12/6 NW12 50M BLK/GN



General Information	
Extended Product Type	XSOLT-12BG.50
Product ID	7TAA292240R0314
EAN	7630030282027
Catalog Description	CONDUIT FINE PA12/6 NW12 50M BLK/GN
Long Description	Fine Profile Three Layer Corrugated Medium-Wall Highly Flexible Conduit, (XSOL) Material - Outer Layer - Polyamide 12, Intermediate Layer - Bonding Compound, Inner Layer - Polyamide 6, Color - Outer Layer - Black, Inner Layer - Green, Conduit Size NW - 12, 50 Meters

Additional Information	
Application	Machine
Product Type	Medium Wall Conduit

Ordering	
EAN	7630030282027
UPC	786209977953

Dimensions	
Product Net Depth / Length	50 m

Technical	
Number of Batteries	0
Color	Black
Material	Outer Layer Polamide 12, Inner Layer Polyamide 6

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	50 m
Package Level 1 Height	0 mm 0 in
Package Level 1 Depth / Length	0 mm 0 in
Package Level 1 Width	0 mm 0 in

Certificates and Declarations	
Data Sheet, Technical Information	XSOLT-12BG.50
Instructions and Manuals	XSOLT-12BG.50
Declaration of Conformity - CE	9AKK107680A0674

Classifications	
ETIM 8	EC001175 - Corrugated plastic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

