



PRODUCT-DETAILS

XT3N 250 TMD 125-1250 4p F F InN=50%

XT3N 250 TMD 125-1250 4p F F InN=50%



General Information	
Extended Product Type	XT3N 250 TMD 125-1250 4p F F InN=50%
Product ID	1SDA068063R1
EAN	8015644019648
Catalog Description	XT3N 250 TMD 125-1250 4p F F InN=50%
Long Description	C.BREAKER TMAX XT3N 250 FIXED FOUR-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMD R 125-1250 A NEUTRAL = 50% PHASES

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 56.6 %
Conflict Minerals Reporting Template	9AKK108467A5658

(CMRT)

End of Life Instructions	9AKK108468A2350
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A2294 9AKK108468A7794
---	------------------------------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	c0e0db6b-cd88-4304-b6f7-f8a119473cab Italy (IT)
Simplified SCIP	765da9ec-3a90-4a3e-a3c3-61dcdbbec362 Germany (DE) da135878-9ee3-405a-a184-1053871bafec Netherlands (NL) 57e921e8-8250-442d-8517-e013dfc04d8c Poland (PL) acd58cfb-22fd-4849-98ba-d769b17b450c Netherlands (NL) b0e50be4-5ce6-4a11-9d18-d2673e3edc6c Estonia (EE) 2b92e57f-bc1a-43d9-8e97-94884e171a60 Greece (GR) 55e35f28-783e-4066-a6ff-409a91c83ce2 Portugal (PT) 653b3e12-3054-4cbc-bee5-f2a9d2a46d32 Bulgaria (BG) 3e351811-df20-4e95-ae9a-d21a6698c1f3 Sweden (SE) d2451aee-4ac1-40fd-bdfb-c4560b04baaf Denmark (DK) 9baf24cd-b2df-4fe4-9df4-d7ecb4c39e52 Poland (PL) 97e1e10f-7bd7-4dd9-ae60-01ec508543b7 France (FR) b6ba0099-1760-4e64-b054-cf1b2cf16940 Germany (DE) 78598f1b-e517-40f2-b906-94cdb6480177 France (FR) 8b5d6c5b-afdc-4a92-99d2-70ebdaf6f1cc Netherlands (NL) 2e334930-8a8a-450e-b094-7bb734047272 Spain (ES) a1001863-93d4-42d2-badf-2c3c91e16c59 Germany (DE) 00db376f-7b74-452e-87f8-002cdc1f3f0b Sweden (SE) b577fa08-f769-451b-9a48-caecc8b8264a Germany (DE) aede30d2-5b90-446d-b65d-44e66a960105 Croatia (HR) 26454a13-bcbf-4385-aabe-acf92c768907 Poland (PL) 1a85c228-2abd-4201-b97c-3f40434aa2cc Norway (NO) 57d69b30-0369-4418-b55b-ed97df68b27d Finland (FI) 29b760fd-9a68-49a8-900b-584134590c56 Netherlands (NL) 7e8e06de-3036-4a2c-97ef-fe4290d707be Germany (DE) 1844ec6b-1cfb-41c7-aaf0-039a17aeb262 Netherlands (NL) 4201a92c-13a3-46b5-a170-0d518f093aa2 Czech Republic (CZ)

Ordering

Order Code US and Canada	XT3NEN125AFF000XXX
E-Number (Finland)	3641008
EAN	8015644019648
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	140 mm
Product Net Height	150 mm
Product Net Depth / Length	70 mm
Product Net Weight	2.1 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	155 mm
Package Level 1 Height	190 mm
Package Level 1 Depth / Length	155 mm
Package Level 1 Gross Weight	2.1 kg
Package Level 1 EAN	8015644019648

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Connecting Capacity Main Circuit	Busbar 85..192 mm ²
Current Type	AC/DC
Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	240 cycles per hour 25000 cycle
Number of Poles	4
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 6.6 W
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I _n)	125 A
Rated Frequency (f)	50 / 60 Hz
Rated Voltage (U _r)	690 V
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Rated Instantaneous Short-Circuit Current Setting (I _i)	1250 A
Rated Insulation Voltage (U _i)	800 V
Rated Operational Voltage	690 V AC 500 V DC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(220 V AC) 37.5 kA (230 V AC) 37.5 kA (240 V AC) 37.5 kA (380 V AC) 27 kA (415 V AC) 27 kA (440 V AC) 18.75 kA (500 V AC) 15 kA (525 V AC) 9.75 kA (690 V AC) 3.75 kA

	(250 V DC) 2 Poles in Series 36 kA (500 V DC) 3 Poles in Series 50 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(220 V AC) 50 kA (230 V AC) 50 kA (240 V AC) 50 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 25 kA (500 V AC) 20 kA (525 V AC) 13 kA (690 V AC) 5 kA (250 V DC) 2 Poles in Series 36 kA (500 V DC) 3 Poles in Series 50 kA
Rated Uninterrupted Current (I _u)	250 A
Recommended Screw Driver	Main Circuit M8
Release	TMD
Release Type	TM
Setting Range	87.5...125 A
Short-Circuit Performance Level	N
Standards	IEC60947-2
Sub-type	XT3
Terminal Connection Type	Front
Terminal Type	Bolt
Tightening Torque	8 N·m
Version	F
CAD Dimensional Drawing	1SDH001295R0483

Certificates and Declarations

ATEX Certificate	No certification needed
Data Sheet, Technical Information	1SDC210100D0206 1SDC210099D0206
Declaration of Conformity - CE	9AKK106713A5530
GL Certificate	1SDL000163R0094
LR Certificate	1SDL000163R0100
UL Certificate	No certification needed
VDE Certificate	No certification needed
Dimension Diagram	1SDH000720R0100
Mechanical Drawings	1SDH000720R0100
Wiring Diagram	1SDM000068R0001
Instructions and Manuals	1SDH000720R0001

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q

UNSPSC	39120000
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

