YLS-7.9-840B 1/3



PRODUCT-DETAILS

YLS-7.9-840B

CABLE TIE 250LB 33IN 316SS BALL-LCK



General Information	
Extended Product Type	YLS-7.9-840B
Product ID	7TCG009410R0033
EAN	5414363072966
Catalog Description	CABLE TIE 250LB 33IN 316SS BALL-LCK
Long Description	Ball-Lock 316 Stainless Steel Cable Tie, Uncoated, for Temperatures up to 300 Degrees Celsius (572 F) for Indoor and Outdoor Applications, Suitable for High Temperature Environments, UL/EN/CSA62275 Type 2S Rated for AH-1 Plenum, Length of 1000mm (33.07 Inches), Width of 7.9mm (0.311 Inches), Thickness of 0.26mm (0.01 Inches), Tensile Strength Rating of 1110 Newtons (250 pounds)

Ordering	
E-Number (Finland)	1381481
EAN	5414363072966
UPC	786210749112
Country of Origin	India (IN)
Selling Unit of Measure	each

YLS-7.9-840B 2/3

Dimensions		
Product Net Width	0.311 in	
	7.9 mm	
Product Net Depth /	39.37 in	
Length	1000 mm	

Container Information	
Package Level 1 Units	100 piece
Package Level 1 Width	9.1 in 231 mm
Package Level 1 Height	0.6 in 15 mm
Package Level 1 Depth / Length	16.9 in 429 mm
Package Level 2 Units	1000 piece
Package Level 2 Width	5.9 in 150 mm
Package Level 2 Height	9.4 in 239 mm
Package Level 2 Depth / Length	22 in 559 mm

Application	For Temperatures up to 300 Degrees Celsius (572 F) for Indoor and Outdoor Applications, Suitable for High Temperature Environments
Brand / Label	Ty-Rap
Color	Metallic
Effective Date	20010412
Lock Type	Ball-Lock
Material	316 Stainless Steel
Product Name	STAINLESS STEEL CABLE TIE
Product Type	Stainless Steel
RoHS Date	9AKK108466A7851
Special Functions	Uncoated
Standards	UL E49405
Tensile Strength	250 lb
	1110 N
Thickness	0.01 in
	0.25 mm

Certificates and Declarations		
Data Sheet, Technical	YLS-7.9-840B	
Information		

Classifications	
EC000046 - Cable tie	
EC000046 - Cable tie	
EC000046 - Cable tie	
39121703	
Product Not in WEEE Scope	

YLS-7.9-840B 3/3

IDEA Granular Category Code (IGCC) 5046 >> Stainless Steel Ties

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$

