N2102 PL 1/3



PRODUCT-DETAILS

## N2102 PL

## Switch 2-way Two-way switch with LED exchangeable Silver - Zenit



| N2102 PL   |
|--|
| 2CLA210200N1301  |
| 8427238067209  |
| Switch 2-way Two-way switch with LED exchangeable Silver - Zenit   |
| Color: Silver.<br>Rated voltage: 110 - 250 Vac<br>Rated current: 16 AX.<br>Rated power iLED (230/127 Vac): 200/100 W.<br>Screwless terminals<br>Optional: locator LED lamp N2192.<br>Size: 1 module. |
|  |

| Installation                |                 |
|-----------------------------|-----------------|
| Instructions and<br>Manuals | 2CLX210109N1001 |
| Mounting Type               | Flush Mounted   |
| Type of Fastening           | Engage (Snap)   |

N2102 PL 2/3

| Technical                            |                                |
|--------------------------------------|--------------------------------|
| Data Sheet, Technical<br>Information | 9AKK10103A5108                 |
| Function                             | Function lighting: Orientation |
| Number of Rocker<br>Switches         | 1                              |
| Wiring Configuration                 | Two-way switch                 |
| Actuator Type                        | Rocker/button                  |
| Connection Type                      | Plug Clamp                     |
| Lamp Type                            | LED exchangeable               |
| Illumination                         | Optiona                        |
| Number of Batteries                  | 0                              |
| <br>Electrical                       |                                |
| Rated Voltage (U <sub>r</sub> )      | 250 V                          |
| Rated Current (In)                   | 16 A                           |

| Design               |                          |
|----------------------|--------------------------|
| Design Range         | Zenit                    |
| Surface Finishing    | Decor<br>Matt            |
| Material             | Plastic<br>Thermoplastic |
| Label Space Provided | No                       |
| Color                | Silver                   |

| Material Compliance                               |  |
|---|--|
| RoHS Information                                  | 2CLC210200N1301  |
| RoHS Status                                       | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| REACH Declaration                                 | 9AKK108467A7464  |
| Conflict Minerals<br>Reporting Template<br>(CMRT) | 9AKK108468A3363  |

| Environmental        |                     |
|----------------------|---------------------|
| Ambient Air          | Operation -5 +35 °C |
| Temperature          | Storage -5 +50 °C   |
| Degree of Protection | IP20                |

| Dimensions         |          |
|--------------------|----------|
| Product Net Width  | 22 mm    |
| Product Net Height | 44 mm    |
| Product Net Weight | 0.021 kg |

Maximum Switching

Current

Fluorescent Lamps 16

N2102 PL 3/3

| 2CLA210200N1302 |
|-----------------|
| 2CLA210200N1303 |
|                 |

| Certificates and Declarations |                 |
|-------------------------------|-----------------|
| Declaration of                | 9AKK106930A5900 |
| Conformity - CF               |                 |

| Classifications |  |
|-----------------|--|
| ETIM 9          | EC001590 - Installation switch                             |
| WEEE Category   | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B  | Business To Consumer                                       |

## **Categories**

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Wiring\ Accessories\ -\ Light\ Switch\ Ranges \rightarrow Cover\ Plates\ and\ Control\ Elements \rightarrow Mechanical\ Controls$ 









3605