



PRODUCT-DETAILS

N2262.1 BL

Time switch Electronic White - Zenit



General Information	
Extended Product Type	N2262.1 BL
Product ID	2CLA226210N1101
EAN	8427238068756
Catalog Description	Time switch Electronic White - Zenit
Long Description	Color: White.
	Rated voltage: 230 Vac / 50 Hz
	Power:
	- Incandescent: 40 - 500 W
	- Halogen with transformer: 40 - 400 VA
	- Motors: 40 - 100 VA
	2 wire connection
	Delay setup: 10 sec. to 10 min.
	Overcurrent protection: with fuse
	Indicator LED lamp included
	Operating temperature: 0 - 40°C
	Size: 2 modules.

Installation	
Instructions and Manuals	2CLX816229A1001

Mounting Type	Flush Mounted
Type of Fastening	Engage (Snap)

Technical

Data Sheet, Technical Information	9AKK10103A5108
Minimum Switching Time	0.17 minute [unit of time]
Time Range	0.16 ... 10_MIN\$
Number of Batteries	0

Electrical

Rated Voltage (U _r)	230 V
Rated Current (I _n)	2.1 A
Frequency (f)	50 ... 50 Hz
Power Watt	500 W
Number of Contacts NO	1

Design

Design Range	Zenit
Surface Finishing	Untreated Glossy
Material	Plastic Thermoplastic
RAL Number	RAL 9010 - Pure White
Color	White

Material Compliance

RoHS Information	2CLC226210N1101
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
REACH Declaration	9AKK108467A7464
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Air Temperature	Operation -5 ... +35 °C Storage -5 ... +50 °C
Degree of Protection	IP20

Dimensions

Product Net Width	44 mm
Product Net Height	44 mm
Product Net Depth / Length	42 mm
Product Net Weight	0.069 kg
Built-In Depth (t ₂)	33.5 mm

Ordering	
Replaced Product ID (OLD)	2CLA226200N1101 2CLA226200N1102

Certificates and Declarations	
Declaration of Conformity - CE	9AKK106930A5901

Classifications	
ETIM 9	EC001594 - Time switch clock for domestic switching devices
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Categories
Low Voltage Products and Systems → Wiring Accessories - Light Switch Ranges → Cover Plates and Control Elements → Electronic Controls



360°