




PRODUCT-DETAILS

N2251.8 BL

TV outlet SAT 2 gang White - Zenit



| General Information   |                                                                                  |
|-----------------------|----------------------------------------------------------------------------------|
| Extended Product Type | N2251.8 BL                                                                       |
| Product ID            | 2CLA225180N1101                                                                  |
| EAN                   | 8427238059709                                                                    |
| Catalog Description   | TV outlet SAT 2 gang White - Zenit                                               |
| Long Description      | Color: White.                                                                    |
|                       | TV-R and SAT double outlet - Intermediate.                                       |
|                       | Installation as an intermediate outlet in series connected to each other.        |
|                       | Output connectors (C1 / C2): IEC male 9,52 mm. diam. / IEC female 9,52 mm. diam. |
|                       | Frequency range (I/O / C1 / C2): 5 - 2.400 MHz / 5 - 2.400 MHz / 5 - 2.400 MHz.  |
|                       | Basic loss (FM / TV / SAT): 10,0±1,0 dB / 10,0±1,0 dB / 12,0±2,0 dB.             |
|                       | Through loss (FM / TV / SAT): 2,5±0,5 / 2,5±0,7 / 3,0±1,0.                       |
|                       | Directivity (FM / TV / SAT): >20 / >12 / >5.                                     |
|                       | Isolation (FM / TV / SAT): >45 / >30 / >28.                                      |
|                       | Return loss (VR / FM / TV / SAT): >13 / >13 / >12 / >12.                         |
|                       | DC path (Vdc / mA / Tono): 24 max. / 500 max. / 22 KHz - DiSEqC.                 |
|                       | Size: 2 modules.                                                                 |

| Installation             |                 |
|--------------------------|-----------------|
| Instructions and Manuals | 2CLX210109N1001 |

|                   |               |
|-------------------|---------------|
| Mounting Type     | Flush Mounted |
| Type of Fastening | Engage (Snap) |

Technical

|                                   |                          |
|-----------------------------------|--------------------------|
| Data Sheet, Technical Information | 9AKK10103A5108           |
| Application                       | SAT                      |
| Type of Indicator                 | Without indication field |
| Outlet Orientation                | Straight                 |
| Number of Batteries               | 0                        |

Design

|                   |                          |
|-------------------|--------------------------|
| Design Range      | Zenit                    |
| Surface Finishing | Untreated<br>Glossy      |
| Material          | Plastic<br>Thermoplastic |
| RAL Number        | RAL 9010 - Pure White    |
| Color             | White                    |

Material Compliance

|                                             |                                                                        |
|---------------------------------------------|------------------------------------------------------------------------|
| RoHS Information                            | 2CLC225180N1101                                                        |
| RoHS Status                                 | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| REACH Declaration                           | 9AKK108467A7464                                                        |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363                                                        |

Environmental

|                         |                                                  |
|-------------------------|--------------------------------------------------|
| Ambient Air Temperature | Operation -5 ... +35 °C<br>Storage -5 ... +50 °C |
| Degree of Protection    | IP20                                             |

Dimensions

|                    |          |
|--------------------|----------|
| Product Net Width  | 44 mm    |
| Product Net Height | 44 mm    |
| Product Net Weight | 0.078 kg |

Ordering

|                           |                 |
|---------------------------|-----------------|
| Replaced Product ID (OLD) | 2CLA225180N1102 |
|---------------------------|-----------------|

Certificates and Declarations

|                                |                       |
|--------------------------------|-----------------------|
| Declaration of Conformity - CE | No declaration needed |
|--------------------------------|-----------------------|

| Classifications |                                                            |
|-----------------|------------------------------------------------------------|
| ETIM 9          | EC000018 - Insert/cover for communication technology       |
| WEEE Category   | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B  | Business To Consumer                                       |

| Categories                                                                                                                                           |
|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Low Voltage Products and Systems → Wiring Accessories - Light Switch Ranges → Cover Plates and Control Elements → Data / Telecommunication / Antenna |

