



PRODUCT-DETAILS

N2185.4 BL

USB charger Breakout cable with USB AC

White - Zenit



General Information	
Extended Product Type	N2185.4 BL
Product ID	2CLA218540N1101
EAN	8427238271149
Catalog Description	USB charger Breakout cable with USB AC White - Zenit
Long Description	Color: White.
	Input voltage: 100 - 240 Vac ±10%; 50/60 Hz.
	Input current (max.): 350 mA.
	Output power (max.): 15 W.
	Output voltage USB-A: 5 Vdc (max. 2,4 A).
	Output voltage USB-C: 5 Vdc (max. 3 A).
	Output voltage USB-A+C: 5 Vdc (total max. 3A).
	Power consumption in stand-by: ≤ 70 mW.
Efficiency: > 86%.	
Size: 1 module	

Installation	
Instructions and Manuals	2CLX215509N1001
Mounting Type	Module frame

Technical	
Data Sheet, Technical Information	9AKK107045A9769
Number of Outputs	2
Connection Type	Push-In

Electrical	
Operational Voltage	100 ... 240 V
Output Voltage (U _{out})	5 V
Output Current Maximum (I _{out})	3000 mA
Rated Frequency (f)	50 ... 60 Hz

Design	
Design Range	Zenit
Surface Finishing	Untreated Glossy
Material	Plastic Thermoplastic
RAL Number	RAL 9010 - Pure White
Color	White

Material Compliance	
RoHS Information	2CLC218540N1101
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental	
Degree of Protection	IP20

Dimensions	
Product Net Width	22 mm
Product Net Height	44 mm
Product Net Depth / Length	44 mm
Product Net Weight	45 g

Ordering	
Replaced Product ID (OLD)	2CLA218520N1101 2CLA218520N1103

Classifications

ETIM 9	EC002949 - USB power supply
UNSPSC	39121406
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Categories

Low Voltage Products and Systems → Wiring Accessories - Light Switch Ranges → Cover Plates and Control Elements → Socket Outlets

