



PRODUCT-DETAILS

N2285.3 AN

USB charger Breakout cable with USB AC Anthracite - Zenit



General Information	
Extended Product Type	N2285.3 AN
Product ID	2CLA228530N1801
EAN	8427238271248
Catalog Description	USB charger Breakout cable with USB AC Anthracite - Zenit
Long Description	Color: Anthracite.
	Input voltage: 100 - 240 Vac ±10%; 50/60 Hz.
	Input current (max.): 250 mA.
	Output power (max.): 10,5 W.
	Output voltage USB-A: 5 Vdc (max. 2,1 A).
	Output voltage USB-C: 5 Vdc (max. 2,1 A).
	Output voltage USB-A+C: 5 Vdc (total max. 2,1A).
	Power consumption in stand-by: <= 70 mW.
Efficiency: > 83%.	
Size: 2 modules.	

Installation	
Instructions and Manuals	2CLX215509N1001
Mounting Type	Module frame

Technical	
Data Sheet, Technical Information	9AKK107045A9769
Number of Outputs	2
Connection Type	Push-In

Electrical	
Operational Voltage	100 ... 240 V
Output Voltage (U _{out})	5 V
Output Current Maximum (I _{out})	2100 mA
Rated Frequency (f)	50 ... 60 Hz

Design	
Design Range	Zenit
Surface Finishing	Decor Matt
Material	Plastic Thermoplastic
Color	Anthracite

Material Compliance	
RoHS Information	2CLC228530N1801
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental	
Degree of Protection	IP20

Dimensions	
Product Net Width	22 mm
Product Net Height	44 mm
Product Net Depth / Length	44 mm
Product Net Weight	45 g

Ordering	
Replaced Product ID (OLD)	2CLA228500N1803

Classifications	
------------------------	--

ETIM 9	EC002949 - USB power supply
UNSPSC	39121406
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business

Categories

Low Voltage Products and Systems → Wiring Accessories - Light Switch Ranges → Cover Plates and Control Elements → Socket Outlets

