



PRODUCT-DETAILS

N2285.4 PL

USB charger Breakout cable with USB AC Silver - Zenit



General Information	
Extended Product Type	N2285.4 PL
Product ID	2CLA228540N1301
EAN	8427238271279
Catalog Description	USB charger Breakout cable with USB AC Silver - Zenit
Long Description	Color: Silver.
	Input voltage: 100 - 240 Vac ±10%; 50/60 Hz.
	Input current (max.): 350 mA.
	Output power (max.): 15 W.
	Output voltage USB-A: 5 Vdc (max. 2.4 A).
	Output voltage USB-C: 5 Vdc (max. 3 A).
	Output voltage USB-A+C: 5 Vdc (total max. 3A).
	Power consumption in stand-by: <= 70 mW.
Efficiency: > 86%.	
Size: 2 modules.	
Installation	
Instructions and Manuals	2CLX210109N1001
Mounting Type	Module frame

Technical	
Data Sheet, Technical Information	9AKK107045A9768
Number of Outputs	2
Connection Type	Push-In

Electrical	
Operational Voltage	100 ... 240 V
Output Voltage (U _{out})	5 V
Output Current Maximum (I _{out})	2100 mA
Rated Frequency (f)	50 ... 60 Hz

Design	
Design Range	Zenit
Surface Finishing	Decor Matt
Material	Plastic Thermoplastic
Color	Silver

Material Compliance	
RoHS Status	No declaration needed
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental	
Degree of Protection	IP20

Dimensions	
Product Net Width	22 mm
Product Net Height	44 mm
Product Net Depth / Length	44 mm
Product Net Weight	45 g

Ordering	
Replaced Product ID (OLD)	2CLA228500N1301

Classifications	
ETIM 9	EC002949 - USB power supply
UNSPSC	39121406
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business

Categories

Low Voltage Products and Systems → Wiring Accessories - Light Switch Ranges → Cover Plates and Control Elements → Socket Outlets

