N2224 AN 1/3



PRODUCT-DETAILS

N2224 AN

Door bell Anthracite - Zenit



| General Information | |
|-----------------------|---------------------------------------------------|
| Extended Product Type | N2224 AN |
| Product ID | 2CLA222400N1801 |
| EAN | 8427238068534 |
| Catalog Description | Door bell Anthracite - Zenit |
| Long Description | Color: Anthracite. |
| | Rated voltage: 230 Vac / 50-60 Hz |
| | 4 melodies available |
| | Acoustic power at 1 meter with cover plate: 72 dB |
| | Size: 2 modules. |

| Installation | |
|-----------------------------|-------------------------|
| Instructions and Manuals | 2CLX812409A1001 |
| Mounting Type | Flush mounted (plaster) |

Technical

N2224 AN 2/3

| Information | 9AKK10103A510 |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|
| Sound dB (A) | 72 d |
| Number of Batteries | |
| Electrical | |
| | |
| Current Type | |
| Rated Voltage (U _r) | 0.2 |
| Docian | |
| Design | |
| Design Range | Zeni |
| Surface Finishing | Deco Mat |
| Housing Material | Plasti |
| Material | Plasti Thermoplasti |
| Color | Anthracit |
| Housing Color | Anthracit |
| Material Compliance | |
| RoHS Information | 2CLC222400N180 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 201 |
| | |
| Conflict Minerals Reporting Template | 9AKK108467A746 9AKK108468A336 |
| REACH Declaration Conflict Minerals Reporting Template (CMRT) Environmental Ambient Air Temperature | 9AKK108468A336 Operation -5 +35 % |
| Conflict Minerals Reporting Template (CMRT) Environmental Ambient Air | 9AKK108468A336 Operation -5 +35 ° Storage -5 +50 ° |
| Conflict Minerals Reporting Template (CMRT) Environmental Ambient Air Temperature | 9AKK108468A336 Operation -5 +35 ° Storage -5 +50 ° |
| Conflict Minerals Reporting Template (CMRT) Environmental Ambient Air Temperature Degree of Protection Dimensions Width in Number of | 9AKK108468A336 Operation -5 +35 ° Storage -5 +50 ° IP2 |
| Conflict Minerals Reporting Template (CMRT) Environmental Ambient Air Temperature Degree of Protection Dimensions Width in Number of Modular Spacings | |
| Conflict Minerals Reporting Template (CMRT) Environmental Ambient Air Temperature Degree of Protection Dimensions Width in Number of Modular Spacings Product Net Width | 9AKK108468A336 Operation -5 +35 ° Storage -5 +50 ° IP2 |
| Conflict Minerals Reporting Template (CMRT) Environmental Ambient Air Temperature Degree of Protection | 9AKK108468A336 Operation -5 +35 ° Storage -5 +50 ° IP2 |
| Conflict Minerals Reporting Template (CMRT) Environmental Ambient Air Temperature Degree of Protection Dimensions Width in Number of Modular Spacings Product Net Width Product Net Height | 9AKK108468A336 Operation -5 +35 ° Storage -5 +50 ° IP2 |

N2224 AN 3/3

Declaration of Conformity - CE 9AKK106930A5901

| Classifications | |
|-----------------|------------------------------------------------------------|
| ETIM 9 | EC000131 - Bell |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Wiring\ Accessories\ -\ Light\ Switch\ Ranges \rightarrow Cover\ Plates\ and\ Control\ Elements \rightarrow Door\ Entry\ /\ Signalisation$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Wiring\ Accessories\ -\ Light\ Switch\ Ranges \rightarrow Cover\ Plates\ and\ Control\ Elements \rightarrow Multimedia\ Devices$

