

Dati tecnici dei minicanali

Minitrunkings data table

Coperchio standard Standard cover	Coperchio avvolgente Wrapping cover	Dimensioni esterne	Sezioni scomparti				Ø Max inscrivibile			N. conduttori inseribili tipo N07V-K			
		b x h	Compartments cross section				Ø Max insertable			N. of insertable cables type N07V-K			
		External dimensions	mm ²				mm			mm ²			
		b x h	1	2	3	TOT	1	2	3	1,5	2,5	4	6

K1010		12 x 10 mm	89			89	8,9			6	3	3	1
K1022	KDU1022	21 x 10 mm	115			115	7			5	4	3	2
	KDU1030	30 x 10 mm	175			175	7			8	6	5	3
K1031		30 x 10 mm	75	75		150	7	7		6	5	3	2
K1515		15 x 15 mm	150			150	11			7	5	4	3
K1818	KDU1818	18 x 18 mm	215			215	13			11	7	5	4
K1825		25 x 18 mm	290			290	15			12	10	7	6
K1830	KDU1830	30 x 18 mm	385			385	16			20	13	11	8
K1831	KDU1831	30 x 18 mm	180	180		360	12	12		17	12	8	7
K1841		40 x 18 mm	245	245		490	15	15		24	16	12	8
	KDU1851	50 x 18 mm	315	315		630	15	15		33	20	15	12
K1852	KDU1852	50 x 18 mm	190	200	190	580	13	13	13	29	19	14	12
K2530		30 x 25 mm	545			545	22			29	20	15	12
K2540		40 x 25 mm	765			765	22			41	29	22	18
K2541		40 x 25 mm	345	345		690	17	17		34	23	18	14
K3030		30 x 30 mm	735			735	27			38	27	20	16
K4040		40 x 40 mm	1.255			1.255	35			64	44	35	27

LCD51	10 x 5 mm	20				20	2,5			2	-	-	-
LCD71 - LCD0712	12 x 7 mm	45				45	4,5			3	2	2	1
LCD86	10 x 10 mm	60				60	6,5			5	3	2	2
LCD94 - LCD1015	15 x 10 mm	95				95	8,0			7	5	5	3
LCD96	13 x 13 mm	115				115	10			11	8	6	4
LCD98	21 x 10 mm	140				140	7,5			11	9	7	4
LCD101	17 x 17 mm	200				200	14			20	15	10	8

LCR0712.3	12x7 mm	47				47	5			2	1	1	-
LCR1515.3	15x15 mm	143				143	10			10	6	5	2
LCR2020.3	20x20 mm	299				299	17			21	14	11	6
LCR2035.3	33x18 mm	472				472	16			37	25	17	9

						MIN	MAX						
KC45	8x6 mm					4	5,5						
KC57	10x7 mm					5	7,5						
KC81	11x9 mm					7	9,5						
KC91	12x10 mm					9	11						