

Innovative lampadine led con attacco R7s e dimensioni adatte a sostituire le tradizionali lampadine alogene. Grazie alla particolare posizione dei led, queste lampade sono in grado di diffondere la luce a 360°, e possono perciò essere montate in quasi tutti gli apparecchi con doppio attacco, senza nessun intervento di modifica dell'apparecchio. Queste lampade possono essere dimmerate grazie all'utilizzo di varialuce per led (vedi pag. 80).

CORTA: 78 mm

SOTTILE

- Accensione istantanea
- Custodia: in vetro + ceramica
- Led ad alta potenza
- Dimmerabile
- Resa cromatica: > 80
- Efficienza luminosa: 115 lm/W
- Vita media: 20.000 ore
- Classe d'isolamento: II 
- Grado di protezione: IP 20, per uso all'interno
- Dimensioni: Ø 15x78 mm



Innovative LED bulbs with R7s base and sizes suited to replace traditional halogen bulbs. Thanks to the particular position of the LEDs, these lamps are able to diffuse the light to 360°, and can therefore be mounted in almost all devices with double base, without having to make any changes to the device. These bulbs can be dimmed through the use of dimmer for LEDs (see page 80).

SHORT: 78 mm

THIN

- Instant power on
- Housing: glass + ceramic
- High brightness LED
- Dimmable
- Colour rendering: > 80
- Luminous efficiency: 115 lm/W
- Average life: 20,000 hours
- Insulation class: II 
- Protection degree: IP 20, for indoor use
- Dimensions: Ø 15x78 mm

ARTICOLO Item	ATTACCO Base	VOLT	WATT	LUMEN	TEMP. COL. Colour Temp.	EQ. INCAND.	APERT. FASCIO Beam angle	
*SD716.D	R7s	220-240V~50 Hz	5W	570	4.000°K	75W	360°	10/100
*SD716.WW	R7s	220-240V~50 Hz	5W	520	3.000°K	75W	360°	10/100

LUNGA: 118 mm

SOTTILE

- Accensione istantanea
- Custodia: in vetro + ceramica
- Led ad alta potenza
- Dimmerabile
- Resa cromatica: > 80
- Efficienza luminosa: 110 lm/W
- Vita media: 20.000 ore
- Classe d'isolamento: II 
- Grado di protezione: IP 20, per uso all'interno
- Dimensioni: Ø 15x118 mm



LONG: 118 mm

THIN

- Instant power on
- Housing: glass + ceramic
- High brightness LED
- Dimmable
- Colour rendering: > 80
- Luminous efficiency: 110 lm/W
- Average life: 20,000 hours
- Insulation class: II 
- Protection degree: IP 20, for indoor use
- Dimensions: Ø 15x118 mm

ARTICOLO Item	ATTACCO Base	VOLT	WATT	LUMEN	TEMP. COL. Colour Temp.	EQ. INCAND.	APERT. FASCIO Beam angle	
*SD720.D	R7s	220-240V~50 Hz	9W	1000	4.000°K	100W	360°	10/100
*SD720.WW	R7s	220-240V~50 Hz	9W	900	3.000°K	100W	360°	10/100