

- Lampadine a bassa intensità luminosa
- Ideali per creare una calda atmosfera
- Bulbo interamente in vetro brunito
- Led a filamento allungato
- Miscela di gas all'interno del bulbo: migliora le prestazioni ed allunga la vita
- Circuito di controllo con componenti integrati in SMD: aumenta la stabilità di corrente e tensione
- Resa cromatica: >80
- Efficienza luminosa: >100 lm/W
- Vetro di primissima qualità
- Vita media: 15.000 ore
- Virola con finitura nichelata
- Classe d'isolamento: II
- Grado di protezione IP20, per uso all'interno

- Low light intensity bulbs
- Ideal for creating a warm atmosphere
- Bulb entirely in burnished glass
- Elongated filament LED
- Gas mixture inside the bulb: improves performance and extends life
- Control circuit with integrated components in SMD: increase current and voltage stability
- Colour rendering: >80
- Luminous efficiency: >100 lm/W
- Highest quality glass
- Average life: 15,000 hours
- Ferrul with nickel finish
- Insulation class: II
- Protection degree: IP20, for indoor use



GOCCIA I STANDARD

Dimensioni | Dimensions: 60 x 102 mm

Peso | Weight: 40 gr

ARTICOLO Item	ATTACCO Base	VOLT	WATT	LUMEN	TEMP. COL. Colour Temp.	EQ. INCAND.	APERT. FASCIO Beam angle	
*VNL60.XW	E27	220-240V~50 Hz	2W	200	2.200°K	25W	360°	10/25



PERA I PEAR

Dimensioni | Dimensions: 64 x 138 mm

Peso | Weight: 45 gr

ARTICOLO Item	ATTACCO Base	VOLT	WATT	LUMEN	TEMP. COL. Colour Temp.	EQ. INCAND.	APERT. FASCIO Beam angle	
*VNL64.XW	E27	220-240V~50 Hz	4W	350	2.200°K	35W	360°	10/25



GLOBO I GLOBE

Dimensioni | Dimensions: 80 x 115 mm (VNL80) - 95 x 133 mm (VNL95) - 125 x 178 mm (VNL125)

Peso | Weight: 45 gr (VNL80) - 50 gr (VNL95) - 100 gr (VNL125)

ARTICOLO Item	ATTACCO Base	VOLT	WATT	LUMEN	TEMP. COL. Colour Temp.	EQ. INCAND.	APERT. FASCIO Beam angle	
*VNL80.XW	E27	220-240V~50 Hz	2W	200	2.200°K	25W	360°	5/25
*VNL125.XW	E27	220-240V~50 Hz	4W	350	2.200°K	35W	360°	5/20