



Rivelatori filari da incasso Wired flush mounted detectors

Descrizione Description		Info	€	□	□	517
 AF441062  AF449062  AF445062  AF442062  AF443062	AF441062 Rivelatore via filo IR-P da incasso. Assorbimento 7mA. Portata 10m. Serie Domus 100. <i>Wired PIR flush mounted detector. Consumption range 7mA. Range 10 m. Domus 100 series.</i>			1	1	
	AF442062 Come sopra. Serie Life 44. <i>See above. Life 44 series.</i>			1	1	
	AF443062 Come sopra. S44 serie Allumia. <i>See above. S44 Allumia series.</i>			1	1	
	AF445062 Come sopra. S44 serie Tekla. <i>See above. S44 Tekla series.</i>			1	1	
	AF449062 Come sopra. S44 serie Class (RAL 1013). <i>See above. S44 Class series (RAL 1013).</i>			1	1	

Nota: prevedere un contatto ausiliario per la protezione antirimozione del dispositivo.
Note: please provide an auxiliary contact to ensure the tamper protection of the device.

DOMOTICA
HOME AUTOMATION

Rivelatori filari volumetrici da parete Wired volumetric wall mounted detectors

Descrizione Description		Info	€	□	□
 AF962  AF963N	AF962 Rivelatore via filo IR-P. Contaimpuls. Portata 15m. Assorbimento 7mA. <i>Wired PIR detector. Impulse counter. 15m range. 7mA current consumption.</i>			1	1
	AF963N Rivelatore doppia tecnologia con antiaccecamento. Assorbimento 30mA. Fornito con snodo. <i>Dual technology detector with anti-blinding. 30mA current consumption. Joint included.</i>			1	1
	AF961 Snodo per rivelatori a parete. Per AF962, AF968R-DB e AF974R-DB. <i>Adjustable joint for detectors. For AF962, AF968R-DB and AF974R-DB.</i>			1	10

GESTIONE ALBERGHERIA
HOTEL MANAGEMENT SYSTEMS

DIVISIONE SICUREZZA
SAFETY-SECURITY

Rivelatori radio volumetrici da parete Wireless volumetric wall mounted detectors



Descrizione Description		Info	€	□	□
 AF968R-DB	AF968R-DB Rivelatore IR-P via radio. Trasmissione in doppia frequenza, Dual Band. Dimensioni: 70x140x40mm <i>PIR radio detector. Dual band transmission. Dimensions: 70x140x40mm</i>			1	1
	AF961 Snodo per rivelatori a parete. Per AF962, AF968R-DB e AF974R-DB. <i>Adjustable joint for detectors. For AF962, AF968R-DB and AF974R-DB.</i>			1	10

