

78BA-AS

chiavi poligonali a percussione antiscintilla

• Misure in pollici

		art.		L mm	Ø mm	S mm	g	
		000780908	78BA-AS 11/16	11/16	145	32,0	12,0	210
		000780909	78BA-AS 3/4	3/4	145	32,0	12,0	200
		000780935	78BA-AS 7/8	7/8	155	38,0	13,0	245
		000780936	78BA-AS 15/16	15/16	165	42,0	14,0	250
★		000780937	78BA-AS 31/32	31/32	165	42,0	14,0	250
		000780938	78BA-AS 1"	1	175	46,0	16,0	350
★		000780939	78BA-AS 1.1/16	1.1/16	175	46,0	16,0	350
		000780940	78BA-AS 1.1/8	1.1/8	180	50,0	16,0	455
		000780941	78BA-AS 1.3/16	1.3/16	185	50,0	16,0	475
		000780910	78BA-AS 1.1/4	1.1/4	177	54,0	23,5	570
★		000780954	78BA-AS 1.5/16	1.5/16	200	55,0	18,0	755
★		000780911	78BA-AS 1.3/8	1.3/8	205	58,0	19,0	560
		000780912	78BA-AS 1.7/16	1.7/16	208	60,0	26,5	780
★		000780913	78BA-AS 1.1/2	1.1/2	215	61,0	19,5	790
★		000780947	78BA-AS 1.9/16	1.9/16	225	64,0	20,0	755
★		000780962	78BA-AS 1.11/16	1.11/16	225	64,0	20,0	755
		000780914	78BA-AS 1.5/8	1.5/8	225	67,0	26,0	950
★		000780963	78BA-AS 1.3/4	1.3/4	235	73,0	22,0	1020
		000780916	78BA-AS 1.13/16	1.13/16	243	74,0	28,0	1235
		000780915	78BA-AS 1.7/8	1.7/8	235	73,0	22,0	990
		000780918	78BA-AS 2	2	254	78,0	28,5	1500
		000780920	78BA-AS 2.3/16	2.3/16	264	84,0	30,0	1685
		000780922	78BA-AS 2.3/8	2.3/8	275	91,5	30,0	1960
★		000780924	78BA-AS 2.9/16	2.9/16	286	99,5	31,5	2400
★		000780926	78BA-AS 2.15/16	2.15/16	311	112,5	33,5	3110
★		000780928	78BA-AS 3.1/8	3.1/8	325	118,0	35,5	3500
★		000780930	78BA-AS 3.1/2	3.1/2	355	130,0	39,0	4600



Strumenti adatti a uso battere-ritiro (battering) e non devono essere usati in contatto con materiali di natura o in cui si possa verificare l'esplosione.

Les outils sont adaptés à l'usage de battage et ne doivent pas être utilisés en contact avec des matériaux susceptibles de provoquer une explosion.

These spanners are suitable for use in contact with materials which do not produce sparks.

Spanners can not be used with flammable or explosive materials.

