

DIN 3118

- Bocche aperte per la manovra di raccordi di impianti idraulici, oleodinamici ed aria compressa.

		art.	 mm	L mm	Ø mm	Ø1 mm	A mm	A1 mm	S mm	S1 mm	 g	
○		000940008	94 8X10	8x10	140	17,8	19,3	6,0	7,0	6,5	7,5	40
○		000940009	94 9X11	9x11	153	19,4	21,4	7,0	9,0	8,0	8,5	49
○		000940010	94 10X11	10x11	153	19,4	21,4	7,0	9,0	8,0	8,5	70
○		000940011	94 11X13	11x13	175	21,4	23,5	9,0	8,5	8,5	10,5	80
○		000940012	94 12X14	12x14	175	22,8	25,3	9,0	11,0	8,5	10,5	78
○		000940013	94 13X15	13x15	175	25,7	27,7	10,5	12,1	11,0	11,4	102
		000940014	94 14X15	14x15	175	25,5	27,3	11,0	12,0	10,5	11,0	130
		000940015	94 14X17	14x17	195	27,4	31,4	11,0	14,0	11,0	12,5	140
		000940017	94 17X19	17x19	212	31,2	33,3	14,0	15,0	12,0	13,0	174
		000940019	94 19X22	19x22	228	33,5	38,5	15,0	17,0	13,0	14,0	220
		000940022	94 22X24	22x24	242	38,5	42,0	17,0	18,0	15,0	16,0	314
		000940024	94 24X27	24x27	260	46,6	46,6	18,0	20,0	16,0	17,0	411
		000940030	94 30X32	30x32	300	50,6	52,6	22,0	24,0	19,0	20,5	672
		000940036	94 36X41	36x41	320	61,0	67,5	25,5	32,5	24,5	25,4	772

