

HALOGEN FREE INSULATED TERMINALS "P" RANGE




GENERAL INFORMATION

- UL listed for US and CANADA per UL486A - 486B (File no. E125401)
- The terminals are for use for internal wiring of equipment only.
- The terminals are for use with Cu wire.
- 600 V max. building wiring, 1000 V max. in sign and fixtures.
- The maximum operating temperature is 105 °C.
- Manufactured from electrolytic copper strip, annealed to guarantee optimum ductility electrolytically tin plated to avoid oxidation.
- The unique funnel shape of PC sleeve, a halogen free self extinguishing plastic materials, guarantees total insertion of the conductor strands into the terminal barrel.

INSTALLATION INSTRUCTIONS

- Select the proper connector for the wire size used.
- Select the proper tool as indicated in the table below.
- Strip the cable insulation, to expose a length of conductor as recommended in the table below, taking care not to damage or cut any of the strands.
- Crimp the connector as indicated in the service and maintenance manual of the tool.

TYPE	SHAPE	SLEEVE COLOR CODE	STUD SIZE (in.)	CONDUCTOR mm ² (AWG) 	CABLE STRIP LENGHT mm (in.) 	INSTALLATION TOOLING 	
VP-M2		GREEN	M2 (#3)	0.2 ÷ 0,5 (24 ÷ 20)	6.5 ÷ 7 (0. ÷ 0.)	HP1	
VP-M3			M3 (#4)				
VP-M3.5			M3,5 (#6)				
VP-M4			M4 (#8)				
VP-M5			M5 (#10)				
VP-M6			M6 (1/4")				
VP-U3			M3 (#4)				
VP-U3.5			M3,5 (#6)				
VP-U4			M4 (#8)				
VP-PP12/19							
RP-M2		RED	M2 (#3)	0.25 ÷ 1,5 (22 ÷ 16)	5 ÷ 6 (0.20 ÷ 0.24)	HP5 HP4-R R21	
RP-M3			M3 (#4)				
RP-M3.5			M3,5 (#6)				
RP-M3.5/1			M3,5 (#6)				
RP-M4			M4 (#8)				
RP-M4/1			M4 (#8)				
RP-M5			M5 (#10)				
RP-M6			M6 (1/4")				
RP-M6/1			M6 (1/4")				
RP-M7			M7 (17/64")				
RP-M8			M8 (5/16")				
RP-M10			M10 (3/8")				
RP-M12			M12 (1/2")				
RP-U3			M3 (#4)				
RP-U3.5			M3,5 (#6)				
RP-U3.5/2			M3,5 (#6)				
RP-U4			M4 (#8)				
RP-U4/1			M4 (#8)				
RP-U4/2			M4 (#8)				
RP-U5			M5 (#10)				
RP-U6			M6 (1/4")				
RP-U6/1			M6 (1/4")				
RP-U8			M8 (5/16")				
RP-U10			M10 (3/8")				
RP-U12			M12 (1/2")				
RP-P8							
RP-P10							
RP-P12							
RP-PP12							
RP-PP12/1							
RP-PP12/19							
RP-PP12/23							
RP-PP14							
RP-PP16/23							
RP-PPL30							
RP-PPL46							

TYPE	SHAPE	SLEEVE COLOR CODE	STUD SIZE (in.)	CONDUCTOR mm ² (AWG) 	CABLE STRIP LENGHT mm (in.) 	INSTALLATION TOOLING 	
BP-M2		BLUE	M2 (#3)	1.5 ÷ 2.5 (16 ÷ 14)	5 ÷ 6 (0.20 ÷ 0.24)	HP5 HP4-B R22	
BP-M3			M3 (#4)				
BP-M3.5			M3,5 (#6)				
BP-M3.5/1			M3,5 (#6)				
BP-M4			M4 (#8)				
BP-M5			M5 (#10)				
BP-M6			M6 (1/4")				
BP-M6/1			M6 (1/4")				
BP-M6/2			M6 (1/4")				
BP-M7			M7 (17/64")				
BP-M8			M8 (5/16")				
BP-M10			M10 (3/8")				
BP-M12	M12 (1/2")						
BP-U3			M3 (#4)				
BP-U3.5			M3,5 (#6)				
BP-U3.5/1			M3,5 (#6)				
BP-U4			M4 (#8)				
BP-U4/1			M4 (#8)				
BP-U4/2			M4 (#8)				
BP-U5			M5 (#10)				
BP-U6			M6 (1/4")				
BP-U6/1			M6 (1/4")				
BP-U8			M8 (5/16")				
BP-U10			M10 (3/8")				
BP-U12			M12 (1/2")				
BP-P8							
BP-P10							
BP-P12							
BP-PP12							
BP-PP12/25							
BP-PP12/29							
BP-PP16/25							
BP-PPL30							
BP-PPL46							
GP-M3		YELLOW	M3 (#4)	4 ÷ 6 (16 ÷ 14)	8 ÷ 9 (0.31 ÷ 0.35)	HP5 HP4-G R23	
GP-M3.5			M3,5 (#6)				
GP-M4			M4 (#8)				
GP-M5			M5 (#10)				
GP-M6			M6 (1/4")				
GP-M6/1			M6 (1/4")				
GP-M7			M7 (17/64")				
GP-M8			M8 (5/16")				
GP-M8/1			M8 (5/16")				
GP-M10			M10 (3/8")				
GP-M10/1			M10 (3/8")				
GP-M12			M12 (1/2")				
GP-M14			M14 (9/16")				
GP-M16			M16 (5/8")				
GP-U3.5			M3,5 (#6)				
GP-U4			M4 (#8)				
GP-U5			M5 (#10)				
GP-U6			M6 (1/4")				
GP-U8			M8 (5/16")				
GP-U10			M10 (3/8")				
GP-U10/1			M10 (3/8")				
GP-U12			M12 (1/2")				
GP-U14			M14 (9/16")				
GP-U16			M16 (5/8")				
GP-P10							
GP-P12							
GP-P14							
GP-PP12							
GP-PP17							
GP-PPL46							