



INSULATED CHAIN TERMINALS WITH EASY ENTRY "CP" RANGE



















GENERAL INFORMATIONS

- The terminals are for use for internal wiring of equipment only.
 - The terminals are for use with Cu wire.
 - 600V max. building wiring, 1000V max. in sign and fixtures.
 - The maximum operating temperature is 105°C.
 - Manufactured from electrolytic copper strip, annealed to guarantee optimum ductility and electrolytically tin plated to avoid oxidation.
 - Developed for use with production machinery, to give a quick and reliable crimped joint.
 - The unique shape of PC sleeve, a halogen free self extinguishing plastic material, guarantees total insertion of the conductor strands into the terminal barrel.
 - The internal surface of barrel is rifled to improve contact with conductor strands when crimped and to increase tensile strength.
- The CP range of terminals offers a wide selection of rings, forks, pins and blades, designed to meet ever changing requirements of the end users.

INSTALLATION INSTRUCTIONS

- 1) Select the proper connector for the wire size used.
- 2) Select the proper applicator head as indicated in the table below.
- 3) Strip the cable insulation, to expose a length of conductor as recommended in the table below, taking care not to damage or cut any of the strands.
- 4) Crimp the connector as indicated in the operation and maintenance manual of the tool.

CATALOG NUMBER	TYPE	SLEEVE COLOR CODE	STUD SIZE	CONDUCTOR mm ² (AWG) 	CABLE STRIP LENGTH mm 	INSTALLATION TOOLING & DIE
CRP-M3		RED	M3	0.25 ÷ 1.5 (22 ÷ 16)	5 ÷ 6	ELB-2 ELB-3 ELB-3Y BENCH PRESS & RA-2 RA-3 APPLICATOR HEAD
CRP-M3,5			M3,5			
CRP-M3,5/1			M3,5			
CRP-M4			M4			
CRP-M4/3			M4			
CRP-M5			M5			
CRP-M6			M6			
CRP-M6/1			M6			
CRP-M7			M7			
CRP-M8			M8			
CRP-U3		RED	M3			
CRP-U3,5			M3,5			
CRP-U3,5/2			M3,5			
CRP-U4			M4			
CRP-U4/1			M4			
CRP-U4/2			M4			
CRP-U5			M5			
CRP-U6			M6			
CRP-U6/1	M6					
CRP-U8	M8					
CRP-P8		RED				
CRP-P10						
CRP-P12						
CRP-PP12		RED				
CRP-PP12/1						
CRP-PP12/23						
CRP-PP14						

CATALOG NUMBER	TYPE	SLEEVE COLOR CODE	STUD SIZE	CONDUCTOR mm ² (AWG) 	CABLE STRIP LENGTH mm 	INSTALLATION TOOLING & DIE		
CBP-M3		BLUE	M3	1.5 ÷ 2.5 (16 ÷ 14)	5 ÷ 6	ELB-2 ELB-3 ELB-3Y BENCH PRESS & BA-2 BA-3 APPLICATOR HEAD		
CBP-M3,5			M3,5					
CBP-M3,5/1			M3,5					
CBP-M4			M4					
CBP-M5			M5					
CBP-M6			M6					
CBP-M6/1			M6					
CBP-M7			M7					
CBP-M8			M8					
CBP-U3							M3	
CBP-U3,5	M3,5							
CBP-U4	M4							
CBP-U4/1	M4							
CBP-U4/2	M4							
CBP-U5	M5							
CBP-U6	M6							
CBP-P8								
CBP-P10								
CBP-P12								
CBP-PP12								
CBP-PP12/25								
CGP-M3		YELLOW	M3	4 ÷ 6 (12 ÷ 10)	8 ÷ 9	ELB-2 ELB-3 ELB-3Y BENCH PRESS & GA-2 GA-3 APPLICATOR HEAD		
CGP-M3,5			M3,5					
CGP-M4			M4					
CGP-M5			M5					
CGP-M6			M6					
CGP-M6/1			M6					
CGP-M7			M7					
CGP-M8			M8					
CGP-M8/1			M8					
CGP-U3,5							M3,5	
CGP-U4	M4							
CGP-U5	M5							
CGP-U6	M6							
CGP-P10								
CGP-P12								
CGP-P14								
CGP-PP12								
CGP-PP17								



www.cembre.com



CEMBRE S.p.A.
via Serenissima, 9
25135 Brescia
Italy
Ph +39 030 36921
ufficio.vendite@cembre.com
sales@cembre.com

CEMBRE Ltd.
Dunton Park,
Kingsbury Road,
Curdworth, Sutton Coldfield
West Midlands, B76 9EB
United Kingdom
Ph +44 01675 470440
sales@cembre.co.uk

CEMBRE S.a.r.l.
22 Avenue Ferdinand
de Lesseps
91420 Morangis Cedex
France
Ph +33 01 60 49 11 90
info@cembre.fr

CEMBRE España S.L.U.
Calle Verano 6 y 8
Pl Las Monjas
28850 Torrejón de Ardoz
Madrid - Spain
Ph +34 91 4852580
comercial@cembre.com

CEMBRE GmbH
Geschäftsbereich
Energie- und Bahntechnik
Heidemannstr. 166
80939 München
Germany
Ph +49 89-3580676
info@cembre.de

CEMBRE GmbH
Geschäftsbereich
Industrie und Handel
Boschstraße 7
71384 Weinstadt
Germany
Ph +49 7151-20536-60
info-w@cembre.de

CEMBRE Inc.
Raritan Center Business Park
300 Columbus Circle-S.F.,
Edison, NJ 08837 USA
Ph +1 (732) 225-7415
sales.us@cembre.com
Midwest Office
1051 Perimeter Dr. #470
Schaumburg, IL 60173