

CONNETTORI a "C" PER CRIMPATURA

La serie dei connettori a "C" è composta da 11 modelli con sezioni nominali da 10 mm² a 240 mm².

MATERIALE

rame elettrolitico


Codice Code	Sezione conduttori mm² Conductors section (mm²)		Dimensioni (mm) Size (mm)			Conf. (pz) PHS (pcs)
	passante feed-through	derivato shunted	A	B	C	
CNT-C010015	10	1,5-10	12	12,6	8,4	1/100
CNT-C016015	16	1,5-16	17	19,4	12	1/100
CNT-C025016	25	16-25	17	21,4	13	1/100
CNT-C035025	35	25-35	21	26,6	15,6	1/100
CNT-C050035	50	35-50	26	38	21	1/50
CNT-C070035	70-50	35-70	28	34	21	1/25
CNT-C095050	95	50-95	29	41	26	1/25
CNT-C120050	120	50-120	30	45	28	1/25
CNT-C150120	150	120-150	30	48	28	1/25
CNT-C185185	185	185	32	52	32	1/15
CNT-C240120	240	120-185	32	55	38	1/15

"C" SHAPED CONNECTORS, CRIMPED

The series of "C" shaped connectors is made up of 11 models with rated sections from 10 mm² to 240 mm².

MATERIAL

electrolytic copper



CONNETTORI TESTA TESTA

Connettori testa testa nudi (non isolato) per cavi in alluminio.

Codice Code	Descrizione Description	Dimensioni +3% Dimensions +3%			Conf. (pz) PHS (pcs)
		A	C	J	
CNT-TTN16AL	16mm²	5,4	8,3	26	400
CNT-TTN25AL	25mm²	7,0	9,7	35	200
CNT-TTN35AL	35mm²	8	10,8	40	200
CNT-TTN50AL	50mm²	9,3	13,0	45	100
CNT-TTN70AL	70mm²	11,6	16,0	55	75
CNT-TTN95AL	95mm²	12,9	17,1	60	75
CNT-TTN120AL	120mm²	15,0	19,6	65	50
CNT-TTN150AL	150mm²	16,5	21,2	70	40
CNT-TTN185AL	185mm²	18,5	24,0	75	30
CNT-TTN225AL	225mm²	21,0	27,0	85	15
CNT-TTN240AL	240mm²	22,0	28,6	90	15
CNT-TTN300AL	300mm²	25,0	32,0	100	10

BUTT CONNECTORS

Bare head-to-head connectors (not insulated) for aluminum cables.

