


FASCETTE IN NYLON

Fascette di cablaggio in poliammide (PA6.6) di colore bianco, per applicazioni in ambienti interni, e nero per applicazioni in ambienti esterni. Attraverso il sistema d'aggancio tra dente e cremagliera permettono il fissaggio di vari diametri.

Facilmente installabili manualmente. In caso di applicazione con l'utilizzo di utensile si raccomanda la corretta regolazione di tensione dello stesso proporzionata alla dimensione della fascetta.



NYLON CABLE TIES

White polyamide wiring cable ties (PA6.6), for indoor applications, and black color for outdoor applications. The hooking system between the pawl and the rack permits the fixing of various diameters.


Easy manual installation. In case of a non manual installation, please make sure your tool is regulated for a stress in proportion to the size of the cable tie.



Codice / Code		Dimensione / dimension mm		Conf. (pz)
Bianco / White	Nero / black	A	B	PHS (pcs)
FC08025B	FC08025N	80	25	100
FC10025B	FC10025N	100	25	100
FC14025B	FC14025N	140	25	100
FC16025B	FC16025N	160	25	100
FC20025B	FC20025N	200	25	100
FC15036B	FC15036N	150	36	100
FC20036B	FC20036N	200	36	100
FC25036B	FC25036N	250	36	100
FC30036B	FC30036N	300	36	100
FC37036B	FC37036N	370	36	100
FC16048B	FC16048N	160	48	100
FC20048B	FC20048N	200	48	100
FC25048B	FC25048N	250	48	100
FC30048B	FC30048N	300	48	100
FC37048B	FC37048N	370	48	100
FC43048B	FC43048N	430	48	100
FC53048B	FC53048N	530	48	100
FC20076B	FC20076N	200	76	100
FC30076B	FC30076N	300	76	100
FC37076B	FC37076N	370	76	100
FC45076B	FC45076N	450	76	100
FC53076B	FC53076N	530	76	100
FC78076B	FC78076N	780	76	100

SUPPORTO PER FASCETTE AUTOADESIVE

I supporti per fascette autoadesive sono ideati per supportare cavi leggeri se applicati correttamente su qualsiasi superficie pulita, liscia e priva di grasso.



SELF ADHESIVE TIE SUPPORT

SELF-ADHESIVE TIE SUPPORT is designed to support light weight wire bundles when properly applied on any clean, smooth, grease-free surface. For heavy support, mounting hole is provided for screws.

Codice Code	Dimensioni Dimensions (mm)			Foro montaggio Mounting Hole (Ø mm)	Foro superiore Upper Hole (Ø mm)	Conf. (pz) PHS (pcs)
	A	B	C			
FCB1919B	18,9	18,9	4,6	4,80	4,20	100
FCB1919N	18,9	18,9	4,6	4,80	4,20	100
FCB2727B	26,3	26,3	6,0	5,00	5,60	100
FCB2727N	26,3	26,3	6,0	5,00	5,60	100

