



Sbarra di distribuzione blocco 1fas., 18unità passo, per FAZ-NA, FAZ-RT



**Tipo** Z-SV/UL-16/1P-1TE/18  
**Catalog No.** 104894

## Programma di fornitura

|                           |  |                                                                                                                                                                                                     |
|---------------------------|--|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Funzione di base          |  | sbarra di distribuzione                                                                                                                                                                             |
| Funzione base accessori   |  | Sbarra di distribuzione per interruttore di protezione della linea<br>Sbarra di distribuzione per interruttori differenziali<br>Sbarra di distribuzione per interruttore protettore combinato FI/LS |
| Applicazione              |  | Apparecchiatura per applicazioni industriali ed edifici funzionali di fascia alta                                                                                                                   |
| Tipo di sistema di sbarre |  | monofase                                                                                                                                                                                            |
| Assortimento              |  | Z-SV                                                                                                                                                                                                |

## Dati tecnici secondo ETIM 6.0

|                                                                                                                                                                                                   |  |                 |     |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|-----------------|-----|
| Low-voltage industrial components (EG000017) / Phase busbar (EC000215)                                                                                                                            |  |                 |     |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss8.1-27-37-13-06 [ACN992008]) |  |                 |     |
| Number of phases                                                                                                                                                                                  |  |                 | 1   |
| Number of poles                                                                                                                                                                                   |  |                 | 1   |
| Suitable for number of devices                                                                                                                                                                    |  |                 | 0   |
| Pitch dimensions                                                                                                                                                                                  |  | mm              | 0   |
| Cross section                                                                                                                                                                                     |  | mm <sup>2</sup> | 16  |
| Length                                                                                                                                                                                            |  | mm              | 315 |
| Number of modular spacings                                                                                                                                                                        |  |                 | 1   |
| Rated permanent current I <sub>u</sub>                                                                                                                                                            |  | A               | 0   |
| Type of electric connection                                                                                                                                                                       |  |                 | Pin |
| Insulated                                                                                                                                                                                         |  |                 | Yes |
| Rated surge voltage                                                                                                                                                                               |  | kV              | 9.5 |
| Conditioned rated short-circuit current I <sub>q</sub>                                                                                                                                            |  | kA              | 0   |
| Max. rated operation voltage U <sub>e</sub>                                                                                                                                                       |  | V               | 690 |
| Rated short-time withstand current I <sub>cw</sub>                                                                                                                                                |  | kA              | 0   |
| Suitable for devices with N-busbar                                                                                                                                                                |  |                 | No  |
| Suitable for devices with auxiliary switch                                                                                                                                                        |  |                 | No  |

## Approvazioni

|                                      |  |                                              |
|--------------------------------------|--|----------------------------------------------|
| Product Standards                    |  | IEC/EN 60898; UL 489; CE marking             |
| UL File No.                          |  | E257181                                      |
| UL Category Control No.              |  | NMTR2, DIHS2                                 |
| CSA File No.                         |  | —                                            |
| CSA Class No.                        |  | —                                            |
| North America Certification          |  | UL recognized                                |
| Specially designed for North America |  | Yes, large creepage and creepage distances   |
| Suitable for                         |  | Feeder Circuit, Branch Circuit               |
| Max. Voltage Rating                  |  | Refer to main components FAZ, FAZ-NA, FAZ-RT |
| Degree of Protection                 |  | IEC: IP20, UL/CSA Type: -                    |