



Sbarra di distribuzione blocco 2fas., 6unità passo, per FAZ-NA, FAZ-RT



Tipo Z-SV/UL-16/2P-2TE/6
Catalog No. 104895

Programma di fornitura

Funzione di base		sbarra di distribuzione
Funzione base accessori		Sbarra di distribuzione per interruttore di protezione della linea Sbarra di distribuzione per interruttori differenziali Sbarra di distribuzione per interruttore protettore combinato FI/LS
Applicazione		Apparecchiatura per applicazioni industriali ed edifici funzionali di fascia alta
Tipo di sistema di sbarre		a 2 fasi
Assortimento		Z-SV

Dati tecnici secondo ETIM 6.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss8.1-27-37-13-06 [ACN992008])			
Number of phases			2
Number of poles			2
Suitable for number of devices			0
Pitch dimensions		mm	0
Cross section		mm ²	16
Length		mm	105
Number of modular spacings			2
Rated permanent current I _u		A	0
Type of electric connection			Pin
Insulated			Yes
Rated surge voltage		kV	9.5
Conditioned rated short-circuit current I _q		kA	0
Max. rated operation voltage U _e		V	690
Rated short-time withstand current I _{cw}		kA	0
Suitable for devices with N-busbar			No
Suitable for devices with auxiliary switch			No

Approvazioni

Product Standards		IEC/EN 60898; UL 489; CE marking
UL File No.		E257181
UL Category Control No.		NMTR2, DIHS2
CSA File No.		—
CSA Class No.		—
North America Certification		UL recognized
Specially designed for North America		Yes, large creepage and creepage distances
Suitable for		Feeder Circuit, Branch Circuit
Max. Voltage Rating		Refer to main components FAZ, FAZ-NA, FAZ-RT
Degree of Protection		IEC: IP20, UL/CSA Type: -