



Morsetti di alimentazione, 2,5-35 mm²

Tipo Z-EK/35/UL
Catalog No. 104901

Programma di fornitura

Funzione di base		sbarra di distribuzione
Funzione base accessori		Morsetti di alimentazione
Applicazione		Apparecchiatura per applicazioni industriali ed edifici funzionali di fascia alta
Assortimento		Z-SV

Dati tecnici secondo ETIM 8.0

apparecchi elettrici a bassa tensione (EG000017) / Morsetto per Condotti Sbarre (EC000001)			
Tecnica Di Ar., Elettr., Energia, Tecn. Di Comm., Rete E Proc. Di Conduttura / Impianti Per Installazioni Elettriche Ed Apparecchiature / Morsetto (Salvo Linea Rea) / Morsetto barra collettore (ecI@ss10.0.1-27-14-11-46 [BAA025013])			
spessore della sbarra collettore	mm	0 - 0	
larghezza della sbarra collettore	mm	0 - 0	
adatto per		altri	
larghezza del morsetto	mm	0	
sezione max. del conduttore	mm ²	0	
max. corrente d'esercizio nominale Ie	A	0	
adatto per collegamento conduttore circolare		sì	
adatto per collegamento conduttore di settore		no	
adatto per collegamento conduttore a nastro		no	

Approvazioni

Product Standards		IEC/EN 60898; UL 489; CE marking
UL File No.		E257181
UL Category Control No.		NMTR2, DIHS2
CSA File No.		—
CSA Class No.		—
North America Certification		UL recognized
Specially designed for North America		Yes, large creepage and creepage distances
Suitable for		Feeder circuits, branch circuits
Max. Voltage Rating		Refer to main components FAZ, FAZ-NA, FAZ-RT
Degree of Protection		IEC: IP20, UL/CSA Type: -