



Congiuntore, 4p, rettilineo

Tipo CSDS4
Catalog No. 136286
Alternate Catalog No. CSDS4

Programma di fornitura

Funzione di base			Accessori
accessori			congiuntore
Tipo di collegamento			Morsetto a bullone
Poli			A 4 poli
Forma costruttiva (dimensioni esterne)		mm	rettilineo
da usare con			
utilizzabile per			Sensori DC, 4 poli, collegamento a 2, 3 o 4, M12
Grado di protezione			IP67
Temperatura ambiente			
Funzionamento	9	°C	-40 - +85
Sezioni di collegamento			
flessibile		AWG	24 - 18
flessibile		mm ²	0,25 - 0,75

Verifiche di progetto secondo IEC/EN 61439

Dati tecnici per verifiche di progetto			
Temperatura ambiente di servizio min.		°C	-40
Temperatura ambiente di servizio max.		°C	85

Dati tecnici secondo ETIM 6.0

Sensors (EG000026) / Sensor-actuator connector (EC002062)			
Electric engineering, automation, process control engineering / Connector system / Industry connector / Sensor-actuator connector (sensor technology acc.) (ecl@ss8.1-27-44-01-04 [ACN876008])			
Type of connection socket for actuators and sensors			M12
Model			Male (plug)
Position cable feed			Straight
Number of poles			4
Type of electric connection			Screw connection
Screened			Yes
Core cross section		mm ²	0
Permitted cable diameter		mm	0 - 0
Material housing			Other

Approvazioni

Product Standards			CE marking
-------------------	--	--	------------