



Limitatore di sovratensione completo, tripolare, 280 VCA, 3x10 kA



Tipo SPET2-280/3
Catalog No. 168692
Alternate Catalog No. SPET2-280/3

Programma di fornitura

Prodotti		Scaricatore di sovratensioni
Campo d'impiego		Edificio ad uso abitativo Edificio non ad uso residenziale Superfici libere

Dati tecnici secondo ETIM 6.0

Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)			
Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Surge protection device for power supply systems (ec1@ss8.1-27-13-08-05 [ACN278008])			
System configuration			Other
Type of poles			3
Nominal discharge surge current (8/20)		kA	10
Nominal voltage AC		V	280
Nominal voltage DC		V	0
Max. continuous voltage AC		V	280
Max. continuous voltage DC		V	0
Max. PV-voltage		V	0
Voltage protection level		kV	1.2
Voltage protection level L-N		kV	0
Voltage protection level N-PE		kV	0
Short-circuit-proof			No
Mounting method			DIN rail (top hat rail) 35 mm
Construction size			3 modular spacing
Max. conductor cross section solid (solid, stranded)		mm ²	25
Max. conductor cross section flexible (fine-strand)		mm ²	0
With remote signalling contact			No
Integrated backup fuse			No
Signalling at the device			Optic
Category type 2			Yes
Degree of protection (IP)			IP20