



Limitatore di sovratensione completo, bipolare, 335 VCA, 2x10 kA

Tipo SPET2-335/2
Catalog No. 168696
Alternate Catalog No. SPET2-335/2

Programma di fornitura

Prodotti		Scaricatore di sovratensioni
Campo d'impiego		Edificio ad uso abitativo Edificio non ad uso residenziale Superfici libere

Dati tecnici secondo ETIM 6.0

Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)		
Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Surge protection device for power supply systems (ecI@ss8.1-27-13-08-05 [ACN278008])		
System configuration		Other
Type of poles		2
Nominal discharge surge current (8/20)	kA	10
Nominal voltage AC	V	335
Nominal voltage DC	V	0
Max. continuous voltage AC	V	335
Max. continuous voltage DC	V	0
Max. PV-voltage	V	0
Voltage protection level	kV	1.3
Voltage protection level L-N	kV	0
Voltage protection level N-PE	kV	0
Short-circuit-proof		No
Mounting method		DIN rail (top hat rail) 35 mm
Construction size		2 modular spacing
Max. conductor cross section solid (solid, stranded)	mm ²	25
Max. conductor cross section flexible (fine-strand)	mm ²	0
With remote signalling contact		No
Integrated backup fuse		No
Signalling at the device		Optic
Category type 2		Yes
Degree of protection (IP)		IP20