



**Sbarra di fase, 3Ph+HS, 10qmm, connettore forchetta, 1m**



**Tipo** BB-EVF-10/3P-1MU/2AUX  
**Catalog No.** 168848  
**Alternate Catalog No.** BB-EVF-10/3P-1MU2AUX

Abbildung ähnlich

## Programma di fornitura

|                           |  |                                                                                                                                                                                                                                                                    |
|---------------------------|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Funzione di base          |  | sbarra di distribuzione                                                                                                                                                                                                                                            |
| Funzione base accessori   |  | Sbarra di distribuzione per interruttori differenziali<br>Sbarra di distribuzione per interruttore protettore combinato FI/LS<br>Sbarra di distribuzione per interruttore di protezione della linea<br>Sbarra di distribuzione per protezione contro sovratensioni |
| Applicazione              |  | Apparecchiatura per applicazioni industriali ed edifici funzionali di fascia alta                                                                                                                                                                                  |
| Tipo di sistema di sbarre |  | trifase + HS                                                                                                                                                                                                                                                       |
| Assortimento              |  | BB-EV                                                                                                                                                                                                                                                              |

## Dati tecnici secondo ETIM 6.0

|                                                                                                                                                                                                   |  |                 |      |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|-----------------|------|
| Low-voltage industrial components (EG000017) / Phase busbar (EC000215)                                                                                                                            |  |                 |      |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecI@ss8.1-27-37-13-06 [ACN992008]) |  |                 |      |
| Number of phases                                                                                                                                                                                  |  |                 | 3    |
| Number of poles                                                                                                                                                                                   |  |                 | 3    |
| Suitable for number of devices                                                                                                                                                                    |  |                 | 0    |
| Pitch dimensions                                                                                                                                                                                  |  | mm              | 0    |
| Cross section                                                                                                                                                                                     |  | mm <sup>2</sup> | 10   |
| Length                                                                                                                                                                                            |  | mm              | 1000 |
| Number of modular spacings                                                                                                                                                                        |  |                 | 1    |
| Rated permanent current I <sub>u</sub>                                                                                                                                                            |  | A               | 63   |
| Type of electric connection                                                                                                                                                                       |  |                 | Fork |
| Insulated                                                                                                                                                                                         |  |                 | Yes  |
| Rated surge voltage                                                                                                                                                                               |  | kV              | 4.5  |
| Conditioned rated short-circuit current I <sub>q</sub>                                                                                                                                            |  | kA              | 0    |
| Max. rated operation voltage U <sub>e</sub>                                                                                                                                                       |  | V               | 690  |
| Rated short-time withstand current I <sub>cw</sub>                                                                                                                                                |  | kA              | 0    |
| Suitable for devices with N-busbar                                                                                                                                                                |  |                 | No   |
| Suitable for devices with auxiliary switch                                                                                                                                                        |  |                 | Yes  |