



Sbarra di fase, NET, 10qmm, matita, 1m

Tipo BB-EVP-10/N-2MU
Catalog No. 168862
Alternate Catalog No. BB-EVP-10/N-2MU

Abbildung ähnlich

Programma di fornitura

Funzione di base		sbarra di distribuzione
Funzione base accessori		Sbarra di distribuzione per interruttori differenziali Sbarra di distribuzione per interruttore protettore combinato FI/LS Sbarra di distribuzione per interruttore di protezione della linea Sbarra di distribuzione per protezione contro sovratensioni
Applicazione		Apparecchiatura per applicazioni industriali ed edifici funzionali di fascia alta
Tipo di sistema di sbarre		Conduttore di neutro
Assortimento		BB-EV

Dati tecnici secondo ETIM 6.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecI@ss8.1-27-37-13-06 [ACN992008])			
Number of phases			1
Number of poles			2
Suitable for number of devices			0
Pitch dimensions		mm	36
Cross section		mm ²	10
Length		mm	1000
Number of modular spacings			2
Rated permanent current I _u		A	63
Type of electric connection			Pin
Insulated			Yes
Rated surge voltage		kV	4.5
Conditioned rated short-circuit current I _q		kA	0
Max. rated operation voltage U _e		V	690
Rated short-time withstand current I _{cw}		kA	0
Suitable for devices with N-busbar			Yes
Suitable for devices with auxiliary switch			No