

SCHEDINA TECNICA - FUSE-D01 16A T GL/GG 400VAC E14



Cartuccia fusibile, Bassa tensione, 16 A, AC 400 V, 50 kA, D01, gL/gG, IEC, ritardato



Tipo FUSE-D01 16A T GL/GG 400VAC E14
Catalog No. 16NZ01

Abbildung ähnlich

Programma di fornitura

Assortimento			fusibile
Funzione di base			cartuccia fusibile
campo di validità			Bassa tensione
Corrente nominale d'impiego	I	A	16
Tensione nominale d'impiego			AC 400 V
Grandezza			D01
Classe di funzionamento			gL/gG
potere di apertura		kA	50
Utilizzo			E14 per applicazioni domestiche e industriali generali
Curva caratteristica d'intervento	Classe		ritardato
Standard/Approvazione			IEC
Forma			bottiglia
Standard/Norme			IEC 60269-3 VDE 0636

Dati tecnici secondo ETIM 6.0

Circuit breakers and fuses (EG000020) / D0-system fuse link (EC001642)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Neozed fuse link (ecl@ss8.1-27-14-21-19 [ACN353008])			
Construction size			D01
Nominal rated current		A	16
Nominal rated voltage		V	400
Colour code			Grey
Utilization category			gL/gG (cable protection/equipment protection)